



Reference: 10213515
EAN 13: 3427580631122

CONTACT

Market information
 industryprojects.business@lynx^{eo}.group.com

- Instrumentation cables 300/500(600) V
- CST 74C068
- Zero halogen (SH)
- **Cables installed outside of the containment area (K3)**
- Overall Screen (EG)
- Unarmoured (NA)

STANDARDS

Product IEC 60228

Test IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

APPLICATIONS

These instrumentation cables allow connection to a variety of measurement equipment. Many of them require anti-inductive screen (EMI).

DESIGN

Conductor:

Flexible bare copper (class 5)

Insulation:

Cross-linked halogen free (SH)

Assembling tape (optional):

Overall screen:

Copper wire braid (CWB)

Outer sheath:

Low smoke, zero halogen (LSZH)

Colour: white

Core identification

Black cores printed with white numbers

STANDARD

IEC 60332-3-23(B)

Quality insurance according to RCC-E



Halogen free
 IEC 60754-1



Rated Voltage U_o/U
 (Um)
 300/500 V



Fire retardant
 NF C 32070 C1; IEC
 60332-3-24 (cat.B)



Smoke density
 EN/IEC 61034-2



Electro magnetic
 interference resistance
 Yes



Operating temp.
 -20 ... 60 °C



Max. conductor temp. in
 service
 90 °C

CHARACTERISTICS

Construction characteristics

Conductor material	Plain copper
Type of conductor	Flexible, Classe 5
Insulation	Halogen-free
Screen	Copper Braid
Outer sheath	Halogen free
Halogen free	IEC 60754-1

Dimensional characteristics

Conductor cross-section	1 mm ²
Conductor diameter	1.3 mm
Diameter over insulation	2.58 mm
Diameter over screen	7.0 mm
Minimum outer diameter	8.7 mm
Maximum outer diameter	10.1 mm
Approximate weight	150 kg/km

Electrical characteristics

Rated Voltage U _o /U (U _m)	300/500 V
---	-----------

Usage characteristics

Fire retardant	NF C 32070 C1; IEC 60332-3-24 (cat.B)
Smoke density	EN/IEC 61034-2
Electro magnetic interference resistance	Yes
Operating temperature, range	-20 ... 60 °C
Max. conductor temperature in service	90 °C
Nuclear Classification	Class 1 E Non LOCA/K3

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

- 10 x outer diameter
- To be doubled during laying operations

2 pair cables (QE) assembled as a quad (1, 3, 2, 4)

Marking

LYNXEO 279 Nber of pairs, triads or quads & cross-section Cu EG CST 74 C 068 00 K3 SH 0.3/0.5 (0.6)
 kV YYYY Manufacturing number + metric marking



Halogen free
IEC 60754-1



Rated Voltage U_o/U
(U_m)
300/500 V



Fire retardant
NF C 32070 C1; IEC
60332-3-24 (cat.B)



Smoke density
EN/IEC 61034-2



Electro magnetic
interference resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor temp.in
service
90 °C