



Reference: 10213526
EAN 13: 3427580631238

CONTACT

Market information
 industryprojects.business@lynxgroup.com

- Instrumentation cables 300/500(600) V
- CST 74C068
- Zero halogen (SH)
- **Cables installed outside of the containment area (K3)**
- Overall Screen (EG)
- Unarmoured (NA)

STANDARDS

Produkt IEC 60228

Tests IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

APPLICATIONS

These instrumentation cables allow connection to a variety of measurement equipment. Many of them require anti-inductive screen (EMI).

DESIGN

Conductor:

Flexible bare copper (class 5)

Insulation:

Cross-linked halogen free (SH)

Assembling tape (optional):

Overall screen:

Copper wire braid (CWB)

Outer sheath:

Low smoke, zero halogen (LSZH)

Colour: white

Core identification

Black cores printed with white numbers

STANDARD

IEC 60332-3-23(B)

Quality insurance according to RCC-E



Halogenfrei
 IEC 60754-1



Nennspannung U_o/U
 300 / 500 V



Flammwidrig
 NF C 32070 C1; IEC
 60332-3-24 (cat.B)



Rauchdichte
 EN/IEC 61034-2



Elektromagnetisch
 geschirmt
 Ja



Betriebstemp.
 -20 ... 60 °C



Max. Betriebstemp. am
 Leiter
 90 °C

CHARACTERISTICS

Konstruktionsmerkmale

Leitermaterial	blank
Leitertype	Flexibel, Klasse 5
Isolierung	Halogen-free
Schirm	Copper Braid
Außenmantel	Halogen free
Halogenfrei	IEC 60754-1

Abmessungsmerkmale

Leiterquerschnitt	0,5 mm ²
Leiterdurchmesser	0,9 mm
Durchmesser über Isolierung	2,1 mm
Diameter over screen	16,5 mm
Außendurchmesser Mindestwert	20,3 mm
Maximaler Außendurchmesser	22,4 mm
Nettogewicht ca.	525 kg/km

Elektrische Eigenschaften

Nennspannung U ₀ /U	300 / 500 V
--------------------------------	-------------

Anwendungsmerkmale

Flammwidrig	NF C 32070 C1; IEC 60332-3-24 (cat.B)
Rauchdichte	EN/IEC 61034-2
Elektromagnetisch geschirmt	Ja
Betriebstemperatur	-20 ... 60 °C
Max. Betriebstemperatur am Leiter	90 °C
Nuclear Classification	Class 1 E Non LOCA/K3

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

2 pair cables (QE) assembled as a quad (1, 3, 2, 4)

Marking

LYNXEO 279 Nber of pairs, triads or quads & cross-section Cu EG CST 74 C 068 00 K3 SH 0.3/0.5 (0.6)
kV YYYY Manufacturing number + metric marking



Halogenfrei
IEC 60754-1



Nennspannung U₀/U
300 / 500 V



Flammwidrig
NF C 32070 C1; IEC
60332-3-24 (cat.B)



Rauchdichte
EN/IEC 61034-2



Elektromagnetisch
geschirmt
Ja



Betriebstemp.
-20 ... 60 °C



Max. Betriebstemp. am
Leiter
90 °C