



Reference: 10241545
EAN 13: 3427650143333

CONTACT

Market information
industryprojects.business@lynx
ogroup.com

Halogenfreie, feuerbeständige Energiekabel mit Schirm (Bewehrung) 0,6/1 kV

STANDARDS

Produkt IEC 60228

Installation IEC 60092-350; IEC 60092-353; IEC 60092-360

Tests a; IEC 60331-1 or 2; IEC 60332-1; IEC 60332-3-22; IEC 60754-1; IEC 61034

APPLICATIONS

MPRXCX[®]331 0.6/1 kV armoured fire resistant power and control cables maintain circuit integrity in case of fire by meeting performances requirements from the IEC 60331 series for 180 minutes. They are used for detection and warning systems where enhanced mechanical protection and electrical screening (EMC) is required.

The highly flexible MPRXCX[®]331 FLEXISHIP[®] range is recommended for installations and connections in narrow spaces where an optimal bending radius is required. Designed with halogen-free fire retardant materials, they provide optimum safety for people and maximal asset protection against all risks of fire.

Design

1. Conductor

Stranded bare copper class 2 or class 5 for FLEXISHIP[®]

2. Insulation

Mica + XLPE (cross-linked polyethylene)

3. Inner covering

(lapped)

4. Armouring

Bare copper braid, separator tape (optional)

5. Outer sheath

Polyolefin SHF1
Colour: orange

Example of marking:

LYNXEO 279 MPRXCX 331 or MPRXCX 331 FLEXISHIP 0.6/1 kV 3x1.5

90°C IEC 60092-353 IEC 60332-3-22 Cat. A IEC 60331-2 ww/yy *CE*+ metric marking

Core Identification

1 x: black

2 x: brown-blue

3 x: brown-black-grey

3G: brown-blue-green/yellow

4 x: brown-black-grey-blue

4G: brown-black-grey-green/yellow

> 5 cores: n x: white with printed numbers / nG: white with printed numbers + green/yellow core



Halogenfrei
IEC 60754-1



Leiterflexibilität
KL.5 = feindrätig



Nennspannung U_o/
U
0.6/ 1 (1.2) kV



Feuerbeständig
IEC 60331-1 or -2



Flammwidrig
IEC 60332-3 Cat. A



Rauchdichte
IEC 61034



Korrosivität der
(Brand-)Gase
niedrig, gem. IEC
60754-2



Elektromagnetisch
geschirmt
Ja

CHARACTERISTICS

Konstruktionsmerkmale

Halogenfrei	IEC 60754-1
Leiterflexibilität	KL.5 = feindrätig
Leitermaterial	Kupfer, blank
Isolierung	XLPE + Mica tape
Schutz	Filler (optional)
Außenmantel	Polyolefin
Armierung	blankes Kupfergeflecht
Mantelfarbe	Orange
Mit grün-gelber Ader	Nein

Abmessungsmerkmale

Aderanzahl	3
Leiterquerschnitt	35 mm ²
Außendurchmesser Mindestwert	26,0 mm
Außendurchmesser, nom.	- mm
Maximaler Außendurchmesser	30,5 mm
Nettogewicht ca.	1431 kg/km

Elektrische Eigenschaften

Zulässige Belastbarkeit in Luft	110 A
Nennspannung U ₀ /U	0.6/ 1 (1.2) kV
Prüfspannung	3500 V

Anwendungsmerkmale

Feuerbeständig	IEC 60331-1 or -2
Flammwidrig	IEC 60332-3 Cat. A
Rauchdichte	IEC 61034
Korrosivität der (Brand-)Gase	niedrig, gem. IEC 60754-2
Elektromagnetisch geschirmt	Ja
Betriebstemperatur	-30 ... 80 °C
Max. Betriebstemperatur am Leiter	90 °C



Halogenfrei
IEC 60754-1



Leiterflexibilität
KL.5 = feindrätig



Nennspannung U₀/U
0.6/ 1 (1.2) kV



Feuerbeständig
IEC 60331-1 or -2



Flammwidrig
IEC 60332-3 Cat. A



Rauchdichte
IEC 61034



Korrosivität der
(Brand-)Gase
niedrig, gem. IEC
60754-2



Elektromagnetisch
geschirmt
Ja

OTHER CHARACTERISTICS

Test Voltage

AC between cores..... 3.5 kV AC

Minimum bending radius for fixed installations

- MPRXCX® 331..... 6 x outer diameter
- MPRXCX® 331 FLEXISHIP®..... 5 x outer diameter