

Reference: 10267333  
EAN 13: 3427580846946

#### CONTACT

Market information  
industryprojects.business@lynx<sup>eo</sup>.com  
ogroup.com

## Fire Resistant Armoured cables CR1-C1-C2 RATP Specification K27

### STANDARDS

**Product** IEC 60228; NF C32-310

**Test** NF C32-070/C1; NF C32-070/C2

### DESIGN

#### 1. Conductor

Bare copper - Solid class 1 for cross section < 4mm<sup>2</sup>  
Stranded class 2 for cross section ≥ 4mm<sup>2</sup>

#### 2. Insulation

Mica tape + Silicone rubber

#### 3. Assembly

#### 4. Collective screen

Polyester tape/copper tape/tinned copper drain wire/polyester tape

#### 5. Inner sheath

Halogen free Polyolefin

#### 6. Armour

Non-magnetic stainless steel

#### 7. Sheath

Halogen free Polyolefin  
Colour: orange

Core identification

Pair: white-blue

Each core printed with pair number

Marking

K27 - 600/1000V - Number of cores & cross-section - ARMOURED - MM/YY -  
LYNXEO 279 - Manufacturing n° + metric marking



Halogen free  
IEC 60754-1



Mechanical  
resistance to  
impacts  
Good



Fire resistant  
NF C 32-070 CR1



Fire retardant  
NFC 32070 C1



Flame retardant  
NFC 32070 C2



Smoke density  
IEC 61034-2



Gases corrosivity  
IEC 60754-2



Operating temp.  
-20 ... 70 °C

**CHARACTERISTICS****Construction characteristics**

Conductor material	Plain copper
Type of conductor	Stranded, class 2
Insulation	Mica tape
Insulating material	Silicone
Inner sheath	Polyolefin
Armour type	-
Outer sheath	Halogen free polyolefin
Sheath colour	Orange
Halogen free	IEC 60754-1
With Green/Yellow core	Yes

**Dimensional characteristics**

Number of cores	4
Conductor cross-section	35 mm <sup>2</sup>
Maximum outer diameter	43.0 mm
Approximate weight	3066 kg/km
Minimum outer diameter	- mm

**Electrical characteristics**

DC permissible current rating	- A
Voltage Drop	- V/A.km

**Mechanical characteristics**

Mechanical resistance to impacts	Good
----------------------------------	------

**Usage characteristics**

Fire resistant	NF C 32-070 CR1
Fire retardant	NFC 32070 C1
Flame retardant	NFC 32070 C2
Smoke density	IEC 61034-2
Gases corrosivity	IEC 60754-2
Operating temperature, range	-20 ... 70 °C
Max. conductor temperature in service	90 °C
Oil resistance	Good
Chemical resistance	Good
Rodent protection	Yes