



**Reference:** 10279575  
**EAN 13:** 3427580819667

### FIRE PERFORMANCE CLASS



B2ca-s1a,d0,a1

### CONTACT

Market information  
 industryprojects.business@lynxéogroup.com

These cables are intended for fixed power or lighting circuits in tunnels, stations and subway stations. These B2ca cables comply with RATP K20 specifications .

### STANDARDS

**Producto** EN 50575; EN 60228

**Instalación** NF F 55-625

### APPLICATION

These cables are used for fixed power or lighting installations in tunnels and underground stations.

### FIRE PERFORMANCE

- Flame retardant: according to RATP K20 specification
- Fire retardant: according to RATP K20 specification
- Low smoke: according to RATP K20 specification
- Low toxicity: According to RATP K20 specification
- Low corrosivity: According to RATP K20 specification
- Without Halogen : According to RATP K20 specification

**Reaction to fire: B2ca-s1a, d0, a1**

### DESIGN

- **Conductor:** Bare copper class 1 or 2
- **Insulation:** Cross-linked Polyethylene (XLPE)
- **Assembling:** An inner sheath acting as a filler
- **Outer sheath:** Polyolefin without halogen Colour : black

### Core identification

According to NF F 55625

2x: black - blue

3x: black - grey - brown

3G: black - blue - green/yellow

4x: black - blue - brown - black

4G: black - blue - brown - green/yellow

5G: black - blue - brown - black - green/yellow

≥ 7 conductors: black cores printed with numbers with or without green/yellow



Libre de halógenos



No propagación de la llama



Densidad de los humos  
 IEC 61034-2 & EN 61034-2



Corrosividad de los gases



Max.conductor temp.in service  
 90 °C



Temp. ambiente de utilización  
 -20 ... 60 °C

## CHARACTERISTICS

### Características de construcción

Type of conductor	Stranded, class 2
Material del conductor	Plain copper
Aislamiento	XLPE
Cubierta exterior	Poliolefina libre de halógenos.
Libre de halógenos	-
Con conductor amarillo/verde	Sí

### Características dimensionales

Número de conductores	4
Sección del conductor	25 mm <sup>2</sup>
Diámetro exterior mínimo	- mm
Diámetro exterior máximo	26,0 mm
Peso aproximado	1431 kg/km

### Características de uso

No propagación de la llama	-
Densidad de los humos	IEC 61034-2 & EN 61034-2
Corrosividad de los gases	-
Temperatura máxima del conductor	90 °C
Temperatura ambiente de utilización (rango)	-20 ... 60 °C

## COMPLEMENT

### Bending radius

$r = 8 \times \text{maximum outer diameter}$

## SELLING AND DELIVERY INFORMATION

### Marking

750 V cables: 750 - Nber of cores & cross-section - SH - NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 - Manufacturing number DoP:1000648-FRME + metric marking  
1000 V cables: 1000 - Nber of cores & cross-section - SH - NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 - Manufacturing number DoP:1000648-FRME + metric marking