



Reference: 10552707
Country Ref.: 13-EBE17Z06P-A1
EAN 13: 8054803127985

CONTACT

Market information
 industryprojects.business@lynxgroup.com

servo cables according to Lenze standard for dynamic applications, PUR jacket, shielded, resistant to oils, flame retardant

STANDARDS

Product UL and CSA approval

DESIGN

Conductor
 Bare copper
Core insulation
 from 1 to 2,5 mm²:
 Polyolefin
 from 4 to 10 mm²:
 Polyester
Core stranding
 Power cores and
 signal pair stranded
 with fillers
Core identification
 Power: Black num
 + Yellow/Green
 Signal: Black + White
Shield
 Total shield:
 Tinned copper braid,
 coverage >= 80%
Jacket
 PUR
Colour:
 Orange RAL 2003

NORMATIVE REFERENCES

Oil resistant

IEC 50363-4-1

Flame retardant

IEC 60331-1-2; FT1; UL 1581; EN 50265-2-1



Halogen free
 Yes



Operating temp.
 -5 ... 80 °C



Storage temperature, range
 -30 ... 80 °C



Oil resistance
 EN 50363-10-2



Flame retardant
 IEC/EN 60332-1-2; FT1; UL 1581 FT1

CHARACTERISTICS

Construction characteristics

Conductor material	Bare copper
Construction type	(4G1 + (2x0.5)C)C
Insulation	Polyolefin
Insulation colour	Power: Black num 1-3 + Green/Yellow; Signal: Black-White
Lay Up	power cores and control pairs stranded with filler
Taping	Non woven tape
Shielding	80% tinned copper braid coverage
Outer sheath	PUR
Sheath colour	Orange RAL 2003
Halogen free	Yes

Dimensional characteristics

Outer Diameter	10 mm
Copper content	91 kg/km
Approximate weight	141 kg/km

Electrical characteristics

Rated Voltage U ₀ /U	0.6/1 kV
Test voltage	4000 V

Mechanical characteristics

Bending cycles	2.5 Mio.
Speed	180 m/min
Maximum acceleration	10 m/s ²

Usage characteristics

Field of application	Dynamic
Operating temperature, range	-5 ... 80 °C
Storage temperature, range	-30 ... 80 °C
Minimum dynamic operating bending radius	10 (xD)
Oil resistance	EN 50363-10-2
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1