



**Reference:** 10553018  
**Country Ref.:** 13-DRW22Z04R  
**EAN 13:** 8054803124427

### CONTACT

Market information  
 industryprojects.business@lynxéogroup.com

DeviceNet cables with PVC jacket for fixed installation, shielded, flame retardant

### STANDARDS

**Product** UL and CSA approval

### APPLICATIONS

DeviceNet is one of the world's leading device-level networks for industrial automation. This bus system offers data transmission and power supply in one cable. The special twisting design allows higher bending cycles than competitors traditional parallel twisting.

### Normative references

UL recognized  
 CSA approval

bus



Operating temp.  
 -25 ... 80 °C



Storage temperature, range  
 -40 ... 80 °C



Flame retardant  
 IEC/EN 60332-1-2; FT1; UL 1581 FT1

**CHARACTERISTICS****Construction characteristics**

Construction type	(1x2x0.34+1x2x0.22)C
Conductor material	Stranded tinned copper
Insulation	Foam-skin
Insulation colour	Red, black, white, blue
Drain wire	Stranded tinned copper
Individual screen	Aluminium / Polyester tape
Shielding	70% tinned copper coverage
Taping	Non woven tape
Outer sheath	PVC
Sheath colour	Violet RAL 4001

**Dimensional characteristics**

Nominal outer diameter	7.0 mm
Copper content	28 kg/km
Approximate weight	58 kg/km

**Electrical characteristics**

Rated Voltage U <sub>0</sub> /U	300 V
Characteristic impedance	120 Ohm
Test voltage	1500 V

**Transmission characteristics**

Attenuation at 1 MHz	AWG24 <= 2.00 db/100m AWG18 <= 1.31 db/100m
----------------------	---------------------------------------------

**Usage characteristics**

Field of application	Static
Operating temperature, range	-25 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1