



**Reference:** 10553062  
**Country Ref.:** 13-EBU01Z06P  
**EAN 13:** 8054803123703

#### CONTACT

Market information  
 industryprojects.business@lynx<sup>eo</sup>  
 group.com

Servo cables according to SIEMENS Standard 6FX8008PLUS for extremely dynamic applications, PUR jacket, shielded, resistant to oils, flame retardant, halogen-free

#### STANDARDS

**Product** UL and CSA approval

#### Normative Reference

**UL Recognized / CSA**  
 AWM 80°C - 600V/1000V  
 AWM 80°C - 600V/1000V FT1

#### Oil Resistance:

EN 50363-10-2

#### Flame Retardant:

IEC 60332-1; FT1: UL 1581; EN 50265-2-1

#### Toxicity:

Halogen free

## CHARACTERISTICS

### Construction characteristics

Construction type	(4G50 + (2x1.5)C)C
Conductor material	Stranded bare copper
Insulation	Polyolefin
Insulation colour	Power: U/L1/C/L+ V/L2 W/L3/D/L- Ye/GN; Signal: Black - White
Lay Up	power cores and control pairs stranded with filler
Taping	Non woven tape
Shielding	80% tinned copper braid coverage
Outer sheath	PUR
Sheath colour	Orange RAL 2003
Halogen free	Yes



Halogen free  
 Yes



Operating temp.  
 -30 ... 80 °C



Storage temperature, range  
 -50 ... 80 °C



Oil resistance  
 EN 50363-10-2



Flame retardant  
 IEC/EN 60332-1-2; FT1; UL 1581 FT1

#### Dimensional characteristics

Nominal outer diameter	34.6 mm
Copper content	2397 kg/km
Approximate weight	2760 kg/km

#### Electrical characteristics

Rated Voltage U <sub>0</sub> /U	0.6/1 kV
Test voltage	4000 V

#### Mechanical characteristics

Maximum acceleration	50 m/s <sup>2</sup>
Bending cycles	10 Mio.
Speed	300 m/min

#### Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	10 (xD)
Operating temperature, range	-30 ... 80 °C
Storage temperature, range	-50 ... 80 °C
Oil resistance	EN 50363-10-2
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1



Halogen free  
Yes



Operating temp.  
-30 ... 80 °C



Storage temperature, range  
-50 ... 80 °C



Oil resistance  
EN 50363-10-2



Flame retardant  
IEC/EN 60332-1-2; FT1; UL 1581 FT1