



**Reference:** 10553087  
**Country Ref.:** 13-EBU11G04P  
**EAN 13:** 8054803123208

### CONTACT

Market information  
industryprojects.business@lynxgroup.com

servo motor cables according to SIEMENS standard 6FX8008PLUS for extremely dynamic applications, PUR jacket, shielded, resistant to oils, flame retardant, halogen free

### STANDARDS

**Product** UL and CSA approval

### DESIGN

**Conductor**  
Stranded Bare copper  
**Core insulation**  
Polyolefin  
**Core stranding**  
Power cores stranded with fillers  
**Core identification**  
*Power:*  
U/L1/C/L+ V/L2  
W/L3/D/L- Ye/Gr

**Shield**  
*Total Shield:*  
Tinned copper braid, coverage  $\geq 80\%$

**Jacket**  
PUR  
Colour: Orange RAL 2003  
(available also in black)

### CHARACTERISTICS

#### Normative Reference

**UL recognised / CSA**  
AWM 80°C - 600V/1000V  
AWM 80°C - 600V/1000V FT1

**Oil Resistance:**EN 50363-10-2

**Flame Resistance:**IEC 60331-1-2; FT1; UL1581; EN 50265-2-1

**Toxicity:**Halogen free



Halogen free  
Yes



Operating temp.  
-30 ... 80 °C



Storage temperature, range  
-50 ... 80 °C



Oil resistance  
EN 50363-10-2



Flame retardant  
IEC/EN 60332-1-2; FT1; UL 1581 FT1

## CHARACTERISTICS

### Construction characteristics

Construction type	(4G4)C
Conductor material	Stranded bare copper
Insulation	Polyolefin
Insulation colour	U/L1/C/L + V/L2 W/L3/D/L - Yellow/Green
Lay Up	Power cores stranded with filler
Taping	Non woven tape
Shielding	80% tinned copper braid coverage
Outer sheath	PUR
Sheath colour	Orange RAL 2003
Halogen free	Yes

### Dimensional characteristics

Conductor cross-section	4 mm <sup>2</sup>
Nominal outer diameter	11.7 mm
Copper content	215 kg/km
Approximate weight	300 kg/km

### Electrical characteristics

Rated Voltage U <sub>0</sub> /U	0.6/1 kV
Test voltage	4000 V

### Mechanical characteristics

Maximum acceleration	50 m/s <sup>2</sup>
Bending cycles	10 Mio.
Speed	300 m/min

### Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	7.5 (xD)
Operating temperature, range	-30 ... 80 °C
Storage temperature, range	-50 ... 80 °C
Oil resistance	EN 50363-10-2
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1



Halogen free  
Yes



Operating temp.  
-30 ... 80 °C



Storage temperature, range  
-50 ... 80 °C



Oil resistance  
EN 50363-10-2



Flame retardant  
IEC/EN 60332-1-2; FT1; UL 1581 FT1