



**Reference:** 10553275  
**Country Ref.:** 13-EYS11G04R-A5  
**EAN 13:** 8054803119447

**CONTACT**

Market information  
industryprojects.business@lynxéogroup.com

Servo cables for dynamic applications, PVC jacket, shielded, resistant to oils flame retardant

**STANDARDS**

**Product** UL and CSA approval

**Normative references**

UL recognised / CSA  
AWM 80°C - 600V/1000V  
AWM 80°C - 600V/1000V FT1

**Oil Resistance:**

EN 50363-4-1

**Flame Resistance:**

IEC 60331-1-2; FT1; UL 1581; EN 50265-2-1

**CHARACTERISTICS**

**Construction characteristics**

Construction type	(4G4)C
Conductor material	Stranded bare copper
Insulation	Polyolefin
Insulation colour	U/L1/C/L + V/L2 W/L3/D/L - Yellow/Green
Lay Up	Power cores stranded with filler
Taping	Non woven tape
Shielding	80% tinned copper braid coverage
Outer sheath	PVC
Sheath colour	Orange RAL 2003

**Dimensional characteristics**

Nominal outer diameter	11.9 mm
------------------------	---------



Operating temp.  
-15 ... 80 °C



Storage temperature, range  
-20 ... 80 °C



Oil resistance  
EN 50363-4-1



Flame retardant  
IEC/EN 60332-1-2; FT1; UL 1581 FT1

**Dimensional characteristics**

Copper content	215 kg/km
Approximate weight	270 kg/km

**Electrical characteristics**

Rated Voltage U <sub>0</sub> /U	0.6/1 kV
Test voltage	4000 V

**Mechanical characteristics**

Maximum acceleration	15 m/s <sup>2</sup>
Bending cycles	10 Mio.
Speed	180 m/min

**Usage characteristics**

Field of application	Dynamic
Minimum dynamic operating bending radius	10 (xD)
Operating temperature, range	-15 ... 80 °C
Storage temperature, range	-20 ... 80 °C
Oil resistance	EN 50363-4-1
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1



Operating temp.  
-15 ... 80 °C



Storage temperature, range  
-20 ... 80 °C



Oil resistance  
EN 50363-4-1



Flame retardant  
IEC/EN 60332-1-2; FT1; UL 1581 FT1