



Resolver cables for dynamic application, PVC jacket, shielded, oil resistant, flame retardant

STANDARDS

Product UL and CSA approval

Normative references

Type Approval UL/CSA
 AWM 80°C -30V
 AWM 75°C - 30V FT1

Reference: 10553631
Country Ref.: 13-MHF24P04R-V1
EAN 13: 8054803112325

CONTACT

Market information
 industryprojects.business@lynxéogroup.com

CHARACTERISTICS

Construction characteristics

Construction type	(4x(2x0.25)C)C
Conductor material	Tinned copper
Insulation	Polyethylene
Insulation colour	TAB CP2
Individual screen	Tinned copper braid
Individual sheath	PVC
Shielding	≥85% tinned copper braid coverage
Outer sheath	PVC
Sheath colour	Green RAL 6018

Dimensional characteristics

Nominal outer diameter	9.5 mm
------------------------	--------



Operating temp.
 -10 ... 80 °C



Storage temperature, range
 -40 ... 80 °C



Oil resistance
 EN 50363-4-1



Flame retardant
 IEC/EN 60332-1-2; FT1; UL 1581 FT1

Dimensional characteristics

Copper content	80 kg/km
Approximate weight	135 kg/km

Electrical characteristics

Rated Voltage U ₀ /U	300 V
Test voltage	1500 V

Mechanical characteristics

Maximum acceleration	10 m/s ²
Bending cycles	2.5 Mio.
Speed	180 m/min

Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	10 (xD)
Operating temperature, range	-10 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Oil resistance	EN 50363-4-1
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1



Operating temp.
-10 ... 80 °C



Storage temperature, range
-40 ... 80 °C



Oil resistance
EN 50363-4-1



Flame retardant
IEC/EN 60332-1-2; FT1; UL 1581 FT1