



**Reference:** 10553862  
**Country Ref.:** C1100046409  
**EAN 13:** 8054803107864

### CONTACT

Market information  
 industryprojects.business@lynxéogroup.com

UL-listed tray cables (TC-ER) cables for fixed installation outside and inside cable tray and wind turbines, PVC jacket, shielded, oil resistant, flame retardant, TC-ER and MTW approved, UL Listed. suitable for American and Canadian market

### STANDARDS

**Product** UL 1277; UL 2277; UL and CSA approval

Cables designed for static application, .

#### Applications:

- cable tray in factories in industry
- Industrial sector
- wind turbine application

#### Approvals:

- UL MTW UL1063
- UL TC-ER 90°C 600V UL1277
- UL WTTC 90°C 1000V UL2277
- UL DP-1
- UL AWM 600V
- C(UL) CIC/TC

## CHARACTERISTICS

### Construction characteristics

Construction type	(4G1)C
Conductor material	Annealed copper
Insulation	PVC/Nylon
Insulation colour	Black w. number + yellow/green
Drain wire	Tinned copper
Shielding	≥85% tinned copper braid coverage
Outer sheath	Special PVC compound
Sheath colour	Black

### Dimensional characteristics

Conductor cross-section	1 mm <sup>2</sup>
Number of cores	4



Operating temp.  
-5 ... 90 °C



Flame retardant  
UL 1581 SEC. 1160 AND CSA FT4



Oil resistance  
Yes

**Dimensional characteristics**

Outer Diameter	8.6 mm
Copper content	64 kg/km
Approximate weight	119 kg/km

**Electrical characteristics**

Rated Voltage Uo/U	600 V
Test voltage	2000 V

**Usage characteristics**

Field of application	Fixed installations
Operating temperature, range	-5 ... 90 °C
Minimum bending radius, static (XD)	20
Flame retardant	UL 1581 SEC. 1160 AND CSA FT4
Oil resistance	Yes



Operating temp.  
-5 ... 90 °C



Flame retardant  
UL 1581 SEC. 1160 AND CSA FT4



Oil resistance  
Yes