



Reference: 10554274
Country Ref.: 13-MY21Z12P-N1
EAN 13: 8054803099626

CONTACT

Market information
 industryprojects.business@lynxgroup.com

Measuring systems cables according to Heidenhain standard for dynamic applications, PUR jacket, shielded, resistant to oils, flame retardant, halogen-free

STANDARDS

Product UL and CSA approval

NORMATIVE REFERENCES:

UL-CSA approval

Oil resistance:

IEC 50363-10-2

Flame retardant:

IEC 60332-1-2

FT1

UL 1581

EN 50265-2-1

CHARACTERISTICS

Construction characteristics

Conductor material	Tinned copper
Construction type	(4x2x0.14+4x0.5)C
Insulation	TPE-E
Insulation colour	See Tab
Taping	Soft tape
Shielding	≥85% tinned copper braid coverage
Outer sheath	PUR
Sheath colour	Black
Halogen free	Yes

Dimensional characteristics

Nominal outer diameter	8.5 mm
Copper content	53 kg/km



Halogen free
Yes



Storage temperature, range
-40 ... 80 °C



Operating temp.
-30 ... 80 °C



Oil resistance
EN 50363-10-2



Flame retardant
IEC/EN 60332-1-2; FT1; UL 1581 FT1

Dimensional characteristics

Approximate weight 83 kg/km

Electrical characteristics

Rated Voltage U₀/U 30 V

Test voltage 1500 V

Mechanical characteristics

Maximum acceleration 20 m/s²

Bending cycles 5 Mio.

Speed 240 m/min

Usage characteristics

Field of application Dynamic

Minimum dynamic operating bending radius 10 (xD)

Storage temperature, range -40 ... 80 °C

Operating temperature, range -30 ... 80 °C

Oil resistance EN 50363-10-2

Flame retardant IEC/EN 60332-1-2; FT1; UL 1581 FT1



Halogen free
Yes



Storage temperature, range
-40 ... 80 °C



Operating temp.
-30 ... 80 °C



Oil resistance
EN 50363-10-2



Flame retardant
IEC/EN 60332-1-2; FT1; UL 1581 FT1