



**Reference:** 10554349  
**Country Ref.:** 13-MYS21Z08P-V1  
**EAN 13:** 8054803098124

#### CONTACT

Market information  
 industryprojects.business@lynxgroup.com

Measuring systems cables acc. to SIEMENS® standard 6FX8008PLUS for extremely dynamic applications, PUR jacket, shielded, oil resistant, flame retardant, halogen free

#### STANDARDS

**Product** UL and CSA approval

#### Normative References

**UL Recognized / CSA Approval**

AWM 80°C - 30V

AWM 75°C - 30V FT1

**Oil resistance:**

IEC 50363-10-2

**Hydrolysis resistance (jacket):**

VDE 0472-02

**Flame retardant:**

IEC 60332-1-2; FT1; UL1581:EN 50265-2-1

**Toxicity:**

Halogen free

## CHARACTERISTICS

### Construction characteristics

Construction type	(3x(2x0.14)D+(2x0.5)D)C
Conductor material	Tinned copper
Insulation	Polyolefin
Insulation colour	See Tab
Lay Up	Please request detailed data sheet
Taping	Soft tape
Outer sheath	PUR
Sheath colour	Green RAL 6018
Shielding	≥85% tinned copper braid coverage
Halogen free	Yes



Halogen free  
Yes



Operating temp.  
-30 ... 80 °C



Flame retardant  
IEC/EN 60332-1-2; FT1; UL 1581 FT1



Storage temperature, range  
-50 ... 80 °C



Oil resistance  
EN 50363-10-2

**Dimensional characteristics**

Nominal outer diameter	9.0 mm
Copper content	68 kg/km
Approximate weight	107 kg/km

**Electrical characteristics**

Rated Voltage U <sub>0</sub> /U	30 V
Test voltage	500 V

**Mechanical characteristics**

Maximum acceleration	50 m/s <sup>2</sup>
Bending cycles	5 Mio.
Speed	300 m/min

**Usage characteristics**

Field of application	Dynamic
Minimum dynamic operating bending radius	7.5 (xD)
Operating temperature, range	-30 ... 80 °C
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1
Storage temperature, range	-50 ... 80 °C
Oil resistance	EN 50363-10-2



Halogen free  
Yes



Operating temp.  
-30 ... 80 °C



Flame retardant  
IEC/EN 60332-1-2; FT1; UL 1581 FT1



Storage temperature, range  
-50 ... 80 °C



Oil resistance  
EN 50363-10-2