



Reference: 10554353
Country Ref.: 13-MYS21Z12P-V1
EAN 13: 8054803098049

CONTACT

Market information
 industryprojects.business@lynxgroup.com

Measuring systems cables acc. to SIEMENS® standard 6FX8008PLUS for extremely dynamic applications, PUR jacket, shielded, oil resistant, flame retardant, halogen free

STANDARDS

Product UL and CSA approval

Normative References

UL Recognized / CSA Approval

AWM 80°C - 30V

AWM 75°C - 30V FT1

Oil resistance:

IEC 50363-10-2

Hydrolysis resistance (jacket):

VDE 0472-02

Flame retardant:

IEC 60332-1-2; FT1; UL1581:EN 50265-2-1

Toxicity:

Halogen free

CHARACTERISTICS

Construction characteristics

Construction type	((3x2x0.14)C+4x0.14+2x0.5)C
Conductor material	Tinned copper
Insulation	Polyolefin
Insulation colour	See Tab
Lay Up	Please request detailed data sheet
Taping	Soft tape
Outer sheath	PUR
Sheath colour	Green RAL 6018
Shielding	≥85% tinned copper braid coverage
Halogen free	Yes



Halogen free
Yes



Operating temp.
-30 ... 80 °C



Flame retardant
IEC/EN 60332-1-2; FT1; UL 1581 FT1



Storage temperature, range
-50 ... 80 °C



Oil resistance
EN 50363-10-2

Dimensional characteristics

Nominal outer diameter	8.6 mm
Copper content	65 kg/km
Approximate weight	100 kg/km

Electrical characteristics

Rated Voltage U ₀ /U	30 V
Test voltage	500 V

Mechanical characteristics

Maximum acceleration	50 m/s ²
Bending cycles	5 Mio.
Speed	300 m/min

Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	7.5 (xD)
Operating temperature, range	-30 ... 80 °C
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1
Storage temperature, range	-50 ... 80 °C
Oil resistance	EN 50363-10-2



Halogen free
Yes



Operating temp.
-30 ... 80 °C



Flame retardant
IEC/EN 60332-1-2; FT1; UL 1581 FT1



Storage temperature, range
-50 ... 80 °C



Oil resistance
EN 50363-10-2