



Reference: 10554381
Country Ref.: 13-MYF28P10R-W1
EAN 13: 8054803097486

CONTACT

Market information
industryprojects.business@lynx^{eo}.com

Control cable with polyolefin insulation and PVC jacket

STANDARDS

Product UL and CSA approval

DESIGN

Insulation colour code

10x2x28AWG:

(White+Blue) (White+Yellow) (White+Green)

(White+Red) (White+Violet) (Brown+Blue)

(Brown+Yellow) (Brown+Green) (Brown+Red)

(Brown+Violet)

Normative references

Oil resistant

IEC 50363-4-1 (PVC)

IEC 50363-10-2 (PUR)

Flame retardant

IEC 60332-1-2

FT1

UL 1581

EN 50265-2-1



无卤
非



操作温度
-20 ... 80 °C



存储温度范围
-50 ... 80 °C



耐油
EN 50363-4-1



阻燃 - 火焰
IEC/EN 60332-1-2; FT1; UL 1581 FT1

CHARACTERISTICS

结构特性

结构类型	10 x 2 x 28 AWG
导体材料	镀锡铜线
绝缘	聚烯烃
绝缘色	Wht+Bl - Wht+Ye - Wht+Gre - Wht+Rd - Wht+Vio - Br+Bl - Br+Ye - Br+Gr - Br+Rd - Br+Vio
绞合	Please request detailed data sheet
Taping	Non woven tape
屏蔽	80% tinned copper braid coverage
外护套	聚氯乙烯
护套颜色	蓝紫
无卤	非

尺寸特性

标称外径	6.0 mm
铜含量	40 kg/km
近似重量	54 kg/km

电气特性

Rated Voltage U ₀ /U	30 V
测试电压	1500 V

机械特性

速度	120 m/min
Maximum acceleration	5 m/s ²
弯曲循环	1 Mio.

使用特性

应用类型	动态
最小弯曲半径 - 动态	10 (xD)
操作温度范围	-20 ... 80 °C
存储温度范围	-50 ... 80 °C
耐油	EN 50363-4-1
阻燃 - 火焰	IEC/EN 60332-1-2; FT1; UL 1581 FT1