



Reference: 10554405
Country Ref.: B1600046409
EAN 13: 8054803097004

CONTACT

Market information
industryprojects.business@lynxgroup.com

UL-listed control cables for fixed installation outside and inside cable tray and wind turbines, PVC jacket, unshielded, oil resistant, flame retardant, TC-ER and MTW approved, UL Listed

STANDARDS

Product UL 1277; UL 2277; UL and CSA approval

Cables designed for static application, .

Applications:

- Machine tools
- Wood machines
- Marble working machines
- Robotics
- Industrial sector

Approvals:

UL MTW UL1063

UL TC-ER 90° C 600V UL1277

UL WTTC 90° C 1000V UL2277

UL DP-1

UL AWM 600V UL758

C(UL) C1C/TC

CHARACTERISTICS

结构特性

结构类型	4G6
导体材料	退火铜
绝缘	-
绝缘色	Black w. number + yellow/green
外护套	特殊聚氯乙烯
护套颜色	黑

尺寸特性

导线截面	6 mm ²
芯线数	4



操作温度
-5 ... 90 ° C



阻燃 - 火焰
UL 1581 SEC. 1160 AND CSA FT4



耐油
是

尺寸特性

外径	14 mm
铜含量	230 kg/km
近似重量	408 kg/km

电气特性

Rated Voltage U ₀ /U	600 V
测试电压	2000 V

使用特性

应用类型	固定安装
操作温度范围	-5 ... 90 ° C
最小弯曲半径 – 静态 (XD)	15
阻燃 – 火焰	UL 1581 SEC. 1160 AND CSA FT4
耐油	是



操作温度
-5 ... 90 ° C



阻燃 – 火焰
UL 1581 SEC. 1160 AND CSA FT4



耐油
是