



Reference: 10554593
Country Ref.: B1150026409
EAN 13: 8054803093242

CONTACT

Market information
 industryprojects.business@lynx^{eo}
 ogroup.com

UL-listed control cables for fixed installation outside and inside cable tray and wind turbines, PVC jacket, unshielded, oil resistant, flame retardant, TC-ER and MTW approved, UL Listed

STANDARDS

Product UL 1277; UL 2277; UL and CSA approval

Cables designed for static application, .

Applications:

- Machine tools
- Wood machines
- Marble working machines
- Robotics
- Industrial sector

Approvals:

UL MTW UL1063
 UL TC-ER 90°C 600V UL1277
 UL WTTTC 90°C 1000V UL2277
 UL DP-1
 ULAWM 600V UL758
 C(UL) CIC/TC

CHARACTERISTICS

Construction characteristics

| | |
|--------------------|--------------------------------|
| Construction type | 2x1,5 |
| Conductor material | Annealed copper |
| Insulation | - |
| Insulation colour | Black w. number + yellow/green |
| Outer sheath | Special PVC compound |
| Sheath colour | Black |

Dimensional characteristics

| | |
|-------------------------|---------------------|
| Conductor cross-section | 1.5 mm ² |
| Number of cores | 2 |



Operating temp.
 -5 ... 90 °C



Flame retardant
 UL 1581 SEC. 1160 AND CSA FT4



Oil resistance
 Yes

Dimensional characteristics

| | |
|--------------------|------------|
| Outer Diameter | 7.5 mm |
| Copper content | 29 kg/km |
| Approximate weight | 93.5 kg/km |

Electrical characteristics

| | |
|---------------------------------|--------|
| Rated Voltage U _o /U | 600 V |
| Test voltage | 2000 V |

Usage characteristics

| | |
|-------------------------------------|-------------------------------|
| Field of application | Fixed installations |
| Operating temperature, range | -5 ... 90 °C |
| Minimum bending radius, static (XD) | 15 |
| Flame retardant | UL 1581 SEC. 1160 AND CSA FT4 |
| Oil resistance | Yes |



Operating temp.
-5 ... 90 °C



Flame retardant
UL 1581 SEC. 1160 AND CSA FT4



Oil resistance
Yes