



Reference: 10554609  
Country Ref.: B1150076409  
EAN 13: 8054803092924

### CONTACT

Market information  
industryprojects.business@lynxgroup.com

UL-listed control cables for fixed installation outside and inside cable tray and wind turbines, PVC jacket, unshielded, oil resistant, flame retardant, TC-ER and MTW approved, UL Listed

### STANDARDS

Product UL 1277; UL 2277; UL and CSA approval

Cables designed for static application, .

Applications:

- Machine tools
- Wood machines
- Marble working machines
- Robotics
- Industrial sector

Approvals:

UL MTW UL1063

UL TC-ER 90° C 600V UL1277

UL WTTC 90° C 1000V UL2277

UL DP-1

UL AWM 600V UL758

C(UL) C1C/TC

## CHARACTERISTICS

### 结构特性

结构类型	7G1,5
导体材料	退火铜
绝缘	-
绝缘色	Black w. number + yellow/green
外护套	特殊聚氯乙烯
护套颜色	黑

### 尺寸特性

导线截面	1.5 mm <sup>2</sup>
芯线数	7



操作温度  
-5 ... 90 ° C



阻燃 - 火焰  
UL 1581 SEC. 1160 AND CSA FT4



耐油  
是

### 尺寸特性

外径	10.2 mm
铜含量	101 kg/km
近似重量	199 kg/km

### 电气特性

Rated Voltage U <sub>0</sub> /U	600 V
测试电压	2000 V

### 使用特性

应用类型	固定安装
操作温度范围	-5 ... 90 ° C
最小弯曲半径 – 静态 (XD)	15
阻燃 – 火焰	UL 1581 SEC. 1160 AND CSA FT4
耐油	是



操作温度  
-5 ... 90 ° C



阻燃 – 火焰  
UL 1581 SEC. 1160 AND CSA FT4



耐油  
是