



10554654

STANDARDS

Product UL and CSA approval

Reference: 10554654
 Country Ref.: Q103418E100
 EAN 13: 8054803092023

CONTACT

Market information
 industryprojects.business@lynxéogroup.com

CHARACTERISTICS

(18x0,34)C

Insulation colour	DIN 47100
Taping	Non woven tape
Shielding	85% tinned copper braid coverage

Sheath colour	Grey RAL 7001
---------------	---------------

0.34 mm²

18

8.2 mm

Copper content	80.8 kg/km
()	124 kg/km



Storage temperature, range
 -30 ... 80 °C



Operating temp.
 -5 ... 80 °C



IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1



Oil resistance
 EN 50363 - 4 - 1

Rated Voltage U _o /U	300 V 1500 V
Bending cycles	5 Mio.
Speed	300 m/min
Maximum acceleration	20 m/s ²
Field of application	Dynamic
Storage temperature, range	- 30 ... 80 °C
操作度范	- 5 ... 80 °C
Minimum dynamic operating bending radius	6.5 (xD)
	IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1
Oil resistance	EN 50363 - 4 - 1



Storage temperature, range
- 30 ... 80 °C



Operating temp.
- 5 ... 80 °C



IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1



Oil resistance
EN 50363 - 4 - 1