



**Reference:** 10554910  
**Country Ref.:** Q202508E200  
**EAN 13:** 8054803086909

**CONTACT**

Market information  
 industryprojects.business@lynxéogroup.com

Controlcables with twisted pairs for data and signal transmission. For extremely dynamic and drag-chain application , shielded, TPU-jacket, oil resistant, flame retardant, halogen free, UL and CSA approved

**STANDARDS**

**Product** UL and CSA approval

Cables designed for continuous moving application, high flexible, oil resistance, halogen free

**Applications:**

- Tracksystems for tool machines
- Wood machines
- Automatic lines for assembly
- Handling
- Packaging
- Other applications with moderate stresses

**CHARACTERISTICS**

**Construction characteristics**

Construction type	(8x2x0,25)C
Conductor material	Bare copper
Insulation	Polyolefin
Insulation colour	DIN 47100
Taping	Non woven tape
Shielding	≥85% tinned copper braid coverage
Outer sheath	PUR
Sheath colour	Grey RAL 7001
Halogen free	Yes

**Dimensional characteristics**

Conductor cross-section	0.25 mm <sup>2</sup>
Number of cores	16



Halogen free  
 Yes



Operating temp.  
 -30 ... 80 °C



Storage temperature, range  
 -40 ... 80 °C



Flame retardant  
 IEC/EN 60332-1-2; FT1; UL 1581 FT1



Oil resistance  
 EN 50363-10-2

**Dimensional characteristics**

Outer Diameter	9.3 mm
Copper content	63.3 kg/km
Approximate weight	122 kg/km

**Electrical characteristics**

Rated Voltage Uo/U	300 V
Test voltage	1500 V

**Mechanical characteristics**

Bending cycles	10 Mio.
Speed	600 m/min
Maximum acceleration	60 m/s <sup>2</sup>

**Usage characteristics**

Field of application	Dynamic
Operating temperature, range	-30 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Minimum dynamic operating bending radius	6.5 (xD)
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1
Oil resistance	EN 50363-10-2



Halogen free  
Yes



Operating temp.  
-30 ... 80 °C



Storage temperature, range  
-40 ... 80 °C



Flame retardant  
IEC/EN 60332-1-2; FT1; UL 1581 FT1



Oil resistance  
EN 50363-10-2