



**Reference:** 10555309  
**Country Ref.:** F105012T100  
**EAN 13:** 8054803078942

#### CONTACT

Market information  
 industryprojects.business@lynxéogroup.com

Control cables for dynamic application up to 1000V, PVC jacket, unshielded, oil resistant, flame retardant, UL and CSA approved

#### STANDARDS

**Product** UL and CSA approval

Cables designed for continuous moving application, high flexible, oil resistance.

#### Applications:

- Tracksystems for tool machines
- Wood machines
- Automatic lines for assembly
- Handling
- Packaging
- Other applications with moderate stresses

### CHARACTERISTICS

#### Construction characteristics

Construction type	12G0,50
Conductor material	Bare copper
Insulation	Polyolefin
Insulation colour	Black w. number + yellow/green
Taping	Non woven tape
Outer sheath	PVC
Sheath colour	Grey RAL 7001

#### Dimensional characteristics

Conductor cross-section	0.5 mm <sup>2</sup>
Number of cores	12
Outer Diameter	8.9 mm
Approximate weight	104 kg/km



Operating temp.  
-5 ... 80 °C



Storage temperature, range  
-40 ... 80 °C



Flame retardant  
IEC/EN 60332-1-2; FT1; UL 1581 FT1



Oil resistance  
EN 50363-4-1

**Dimensional characteristics**

Copper content 60 kg/km

**Electrical characteristics**

Rated Voltage U<sub>0</sub>/U 600 V

Test voltage 4000 V

**Mechanical characteristics**

Bending cycles 5 Mio.

Speed 300 m/min

Maximum acceleration 20 m/s<sup>2</sup>

**Usage characteristics**

Field of application Dynamic

Operating temperature, range -5 ... 80 °C

Storage temperature, range -40 ... 80 °C

Minimum dynamic operating bending radius 6.5 (xD)

Flame retardant IEC/EN 60332-1-2; FT1; UL 1581 FT1

Oil resistance EN 50363-4-1



Operating temp.  
-5 ... 80 °C



Storage temperature, range  
-40 ... 80 °C



Flame retardant  
IEC/EN 60332-1-2; FT1; UL 1581 FT1



Oil resistance  
EN 50363-4-1