



Reference: 10555373  
EAN 13: 8054803077662

### CONTACT

Market information  
industryprojects.business@lynx<sup>eo</sup>group.com

Control cables for dynamic application up to 1000V, PVC jacket, unshielded, oil resistant, flame retardant, UL and CSA approved

### STANDARDS

Product UL and CSA approval

Cables designed for continuous moving application, high flexible, oil resistance.

Applications:

- Tracksystems for tool machines
- Wood machines
- Automatic lines for assembly
- Handling
- Packaging
- Other applications with moderate stresses

## CHARACTERISTICS

16G0,75

Insulation colour  
Taping

Black w. number + yellow/green  
Non woven tape

Sheath colour

Grey RAL 7001

0.75 mm<sup>2</sup>

16

10.9 mm

( )

Copper content

179 kg/km

120 kg/km

Rated Voltage U<sub>o</sub>/U

1000 V



Operating temp.  
-5 ... 80 °C



Storage temperature, range  
-40 ... 80 °C



IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1



Oil resistance  
EN 50363 - 4 - 1

	4000 V
Bending cycles	5 Mio.
Speed	300 m/min
Maximum acceleration	20 m/s <sup>2</sup>
Field of application	Dynamic
操作度范	- 5 ... 80 °C
Storage temperature, range	- 40 ... 80 °C
Minimum dynamic operating bending radius	6.5 (xD)
	IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1
Oil resistance	EN 50363 - 4 - 1



Operating temp.  
- 5 ... 80 °C



Storage temperature, range  
- 40 ... 80 °C



IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1



Oil resistance  
EN 50363 - 4 - 1