



Reference: 13-DRY22X02R
Country Ref.: 13-DRY22X02R

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

Interconnecting fieldbus cables for static application

STANDARDS

Product UL and CSA approval

Applications

Bus cable family facilitating interconnections for L2 BUS components.

Normative references

UL/CSA

Flame retardant IEC 60332-1-2; FT1; UL 1581; EN 50265-2-1



Bending factor installed
7.5 (xD)



操作温度
-20 ... 80 °C



存储温度范围
-30 ... 80 °C



阻燃 - 火焰
IEC/EN 60332-1-2; FT1; UL 1581 FT1

CHARACTERISTICS

结构特性

结构类型	(1x2x0, 64/2, 55)C
导体材料	裸铜线
绝缘	泡沫皮
绝缘色	Green - Red
填充物/内护套材料	热塑材料
Taping	Aluminium / Polyester tape
内护套	Thermoplastic compound
屏蔽	80% tinned copper braid coverage
外护套	聚氯乙烯
护套颜色	Violet RAL 4001
绞合	-

尺寸特性

铜含量	27 kg/km
外径	8 mm
近似重量	95 kg/km

电气特性

Rated Voltage U ₀ /U	30 V
测试电压	500 V
特性阻抗	150 Ohm

传输特性

衰减在9.6kHz	2.5 dB/1000m
衰减在38.4kHz	4 dB/1000m
衰减在4MHz	22 dB/1000m
衰减在16MHz	42 dB/1000m

使用特性

应用类型	Static
安装时弯曲系数	7.5 (xD)
操作温度范围	-20 ... 80 °C
存储温度范围	-30 ... 80 °C
阻燃 - 火焰	IEC/EN 60332-1-2; FT1; UL 1581 FT1