



Reference: 13-MYE21Z08R-V1
Country Ref.: 13-MYE21Z08R-V1

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

Measuring systems cables according to LENZE standard for fixed installation, PVC jacket, resistant to oils, flame retardant

STANDARDS

Product UL and CSA listing

NORMATIVE REFERENCES

Oil resistant

IEC 50363-4-1

Flame retardant

IEC 60332-1-2

FT1

UL 1581

EN 50265-2-1



操作温度
-25 ... 80 °C



耐油
EN 50363-4-1



阻燃 - 火焰
IEC/EN 60332-1-2; FT1; UL 1581 FT1

CHARACTERISTICS

结构特性

结构类型	3x (2x0.14) C+2x (0.5) C
导体材料	镀锡铜线
绝缘	聚烯烃
绝缘色	See Tab
线对屏蔽	Tinned copper braid
绞合	Please request detailed data sheet
Taping	Non woven tape
外护套	聚氯乙烯
护套颜色	Green RAL 6018

尺寸特性

标称外径	9.3 mm
铜含量	42 kg/km
近似重量	91 kg/km

电气特性

Rated Voltage U ₀ /U	300 V
测试电压	1500 V

使用特性

应用类型	Static
最小弯曲半径 - 安装	7.5 (xD)
操作温度范围	-25 ... 80 ° C
耐油	EN 50363-4-1
阻燃 - 火焰	IEC/EN 60332-1-2; FT1; UL 1581 FT1