



Reference: 13 - MYI17Z11P - A1
Country Ref.: 13 - MYI17Z11P - A1

CONTACT

Market information
industryprojects.business@lynxgroup.com

Measuring systems cables according to BOSCH REXROTH standard for extremely dynamic applications, PUR jacket, shielded, resistant to oils, flame retardant, halogen - free

STANDARDS

Product UL and CSA approval

Normative Reference

UL Recognized / CSA

AWM 80 ° C - 300V

AWM 75 ° C - 300V FT1

Oil Resistance:

IEC 50363 - 10 - 2

Flame Retardant

IEC 60332 - 1 - 2

FT1

UL 1581

EN 50265 - 2 - 1

Toxicity:

Halogen free

CHARACTERISTICS

(2x1+3x(2x0.25)C+3x0.25)C

Stranded tinned copper

Insulation colour	See Tab
Lay Up	Please request detailed data sheet
Taping	Soft tape
Shielding	85% tinned copper braid coverage
Sheath colour	PUR Orange RAL 2003
Halogen free	
Nominal outer diameter	10.0 mm
Copper content	77 kg/km



Halogen free



Operating temp.
-30 ... 80 ° C



Storage temperature, range
-40 ... 80 ° C



Oil resistance
EN 50363 - 10 - 2



IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1

()	- kg/km
Rated Voltage U _o /U	300 V 1500 V
Maximum acceleration	20 m/s ²
Bending cycles	5 Mio.
Speed	240 m/min
Field of application	Dynamic
Minimum dynamic operating bending radius	7.5 (xD)
操作度范	- 30 ... 80 ° C
Storage temperature, range	- 40 ... 80 ° C
Oil resistance	EN 50363 - 10 - 2
IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1	



Halogen free



Operating temp.
- 30 ... 80 ° C



Storage temperature, range
- 40 ... 80 ° C



Oil resistance
EN 50363 - 10 - 2



IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1