



Reference: 13101504
Country Ref.: 2PN299

CONTACT

Markets and Products Information
rollingstock.business@lynxgroup.com

FIRE RESISTANT CONTROL WIRES

FLAMEX® Fire Resistant control wires TYPE EN 50306-2 maintain circuit integrity in case of fire (according to EN 50200 for 120 minutes) and are fire retardant, low smoke and halogenfree satisfying performance requirements of EN 45545-2 HL3. In addition, FLAMEX® cables withstand the tough working conditions of rolling stock (oil, ozone, temperature variations, etc.).

STANDARDS

Product EN 45545-2 (HL3)

Test EN 50200; EN 50305; EN 50306; IEC 60331-2

DESIGN

1. Conductor

Flexible stranded tinned copper

2. Insulation

Mineral tape as fire barrier

Thin wall halogen-free cross-linked material acc. EN 50306-2

Colour: white

Example of marking: FLAMEX 239 - EDE 2PN299 - TYPE EN 50306-2 - EN 50200 - 300 V - 1x0.5 - M - week/year - batch number

GUIDE TO USE

- Cabling rules are given in EN 50343 and EN 50355
- Permissible current carrying capacities: values and calculation method are given in EN 50343
- Bending radius:
 - Static use: 5 x outer cable diameter
 - For installation and occasional movements: 10 x outer cable diameter



Conductor flexibility
Flexible stranded



Halogen free
EN 60754-1 & EN 60684-2



Rated Voltage U_o/U_i
(Um)
300 / 300 V



Fire resistant
-



Flame retardant
EN 60332-1-2



Fire retardant
EN IEC 60332-3-25
(EN50305)



Smoke density
EN/IEC 61034-2



Gases toxicity
EN 50305-9.2

CHARACTERISTICS**Construction characteristics**

Conductor material	Tin plated copper
Conductor flexibility	Flexible stranded
Insulation	Cross-linked compound
Halogen free	EN 60754-1 & EN 60684-2
Insulation colour	White

Dimensional characteristics

Conductor cross-section	0.5 mm ²
Stranding (No./mm)	
Conductor diameter (mm)	0.95
Minimum cable diameter	1.7 mm
Maximum cable diameter	2 mm
Approximate weight	7.5 kg/km

Electrical characteristics

Rated Voltage U _o /U (U _m)	300 / 300 V
Max. DC resistance of the conductor at 20°C	40.1 Ohm/km

Usage characteristics

Fire resistant	-
Flame retardant	EN 60332-1-2
Fire retardant	EN IEC 60332-3-25 (EN50305)
Smoke density	EN/IEC 61034-2
Gases toxicity	EN 50305-9.2
Operating temperature, range	-40 ... 105 °C
Maximum operating temperature	105 °C
Overload maximum core temperature	125 °C
Chemical resistance	Excellent
Fire load	0.009 kWh/m