

MEASURING SYSTEM CABLE ACC. TO SIEMENS® STANDARD 6FX8008-DC00 (DRIVE CLiQ)

DRIVE CLiQ CABLE ACC. TO SIEMENS® 6FX8008-2DC00 (2x(2x0,22)C +(2x0,38)C)C



Measuring systems cables for very dynamic application MOTIONLINE®

STANDARDS

Product UL and CSA approval

For very dynamic applications; PUR Jacket, screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.

Reference: 44460479
Country Ref.: 6FX8008-2DC00

CONTACT

Market information
 industryprojects.business@lynxeogroup.com



Operating temp.
 -15 ... 80 °C



Storage temperature, range
 -40 ... 80 °C



Flame retardant
 IEC 60332-1-2; UL 1581 FT1



Oil resistance
 DIN EN 50363-10-2 & DIN EN 60811-404

CHARACTERISTICS

Construction characteristics

Construction type	(2x(2x0,22)C+(2x0,38)C)C
Conductor material	Bending-resistant conductor with tinned copper wires
Insulation	TPM with very low capacitance
Insulation colour	1^ Pair: Green+Yellow; 2^ Pair: Pink+Blue
Taping	Copper/Polyester Tape
Screen	Tinned copper braid, coverage ≥ 85%
Outer sheath	PUR
Sheath colour	Grey

Dimensional characteristics

Copper content	37 kg/km
Approximate weight	67 kg/km
Outer Diameter	7.1 mm

Electrical characteristics

Rated Voltage U ₀ /U	30 V
Test voltage	300 V

Mechanical characteristics

Maximum acceleration	20 m/s ²
Bending cycles	5 Mio.
Speed	180 m/min

Usage characteristics

Field of application	Fixed installations
Minimum dynamic operating bending radius	10 (xD)
Operating temperature, range	-15 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404