



Measuring systems cables for fixed installation MOTIONLINE®

STANDARDS

Product UL and CSA approval

For fixed installations; PVC Jacket, screened, resistant to oils and coolants, flame retardant.

Reference: 44479831

CONTACT

Market information
industryprojects.business@lynx
ogroup.com



Storage temperature, range
-40 ... 80 °C



Flame retardant
IEC 60332-1-2; UL 1581 FT1



Oil resistance
EN 50363-4-1

CHARACTERISTICS

Construction characteristics

Construction type	(2x2x0.22)C
Conductor material	Bending-resistant conductor with tinned copper wires
Insulation	TPM with very low capacitance
Insulation colour	1^ Pair: Green+Yellow; 2^ Pair: Pink+Blue
Taping	Copper/Polyester Tape
Screen	Tinned copper braid, coverage ≥ 85%
Outer sheath	PVC
Sheath colour	Grey

Dimensional characteristics

Copper content	28 kg/km
Approximate weight	69 kg/km
Outer Diameter	7 mm

Electrical characteristics

Rated Voltage U ₀ /U	30 V
Test voltage	300 V

Usage characteristics

Field of application	Fixed installations
Minimum dynamic operating bending radius	7.5 (xD)
Storage temperature, range	-40 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	EN 50363-4-1