



For dynamic applications MOTIONLINE® STANDARD

### STANDARDS

**Product** UL and CSA approval

For standard dynamic applications; screened cables; PUR sheath, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC and halogen free, Industry 4.0 ready.

**Reference:** 44495170

### CONTACT

Market information  
[industryprojects.business@lynxogroup.com](mailto:industryprojects.business@lynxogroup.com)



Halogen free  
**Yes**



Operating temp.  
 -30 ... 80 °C



Storage temperature, range  
 -40 ... 80 °C



Flame retardant  
 IEC 60332-1-2; UL 1581 FT1



Oil resistance  
 DIN EN 50363-10-2 & DIN EN 60811-404

**CHARACTERISTICS****Construction characteristics**

Construction type	(4x2xAWG26/19)C
Conductor material	Bending-resistant conductor with bare copper wires
Insulation	Polyolefin
Lay Up	Pairs stranded with fillers
Insulation colour	White/Orange, White/Green, White/Blue, White/Brown
Taping	Plastic aluminium tape
Screen	Tinned copper braid, coverage ≥ 85%
Outer sheath	PUR
Sheath colour	Green RAL 6018
Halogen free	Yes

**Dimensional characteristics**

Outer Diameter	6.8 mm
Copper content	27 kg/km
Approximate weight	54 kg/km

**Electrical characteristics**

Rated Voltage U <sub>o</sub> /U	30 V
Test voltage	500 V
Characteristic impedance	100 Ohm

**Mechanical characteristics**

Bending cycles	1 Mio.
Speed	120 m/min
Maximum acceleration	2 m/s <sup>2</sup>

**Usage characteristics**

Field of application	Dynamic
Minimum dynamic operating bending radius	15 (xD)
Operating temperature, range	-30 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404