



Reference: 44495780

CONTACT

Market information
industryprojects.business@lynxeogroup.com

For dynamic applications MOTIONLINE® STANDARD

STANDARDS

Product UL and CSA approval

For standard dynamic applications; screened cables; PUR sheath, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC and halogen free, Industry 4.0 ready.

Construction

Conductor: Bending - resistant conductor with bare copper wires

Core insulation: Polyolefin

Pair stranding: Pairs stranded with fillers and screened with plastic aluminium foil

Core stranding: Four screened pairs were lay up to the core

Screen: Tinned copper braid, coverage 85% (overall screen)

Jacket: PUR Colour: violet (similar RAL 4001)



Halogen free



Operating temp.
-15 ... 80 °C



Storage temperature, range
-40 ... 80 °C



Oil resistance
IEC 60332 - 1 - 2; UL 1581 FT1
DIN EN 50363 - 10 - 2 & DIN EN 60811 - 404

CHARACTERISTICS

	(4x2xAWG26/19)C
	Bending - resistant conductor with bare copper wires
Lay Up	Four screened pairs were lay up to a core
Insulation colour	White/Orange, White/Green, White/Blue, White/Brown
Taping	
	Tinned copper braid, coverage 85%
	PUR
Sheath colour	Violet RAL 4001
Halogen free	
	8.9 mm
Copper content	40 kg/km
()	88 kg/km
Rated Voltage Uo/U	30 V
	500 V
Characteristic impedance	100 Ohm
Bending cycles	1 Mio.
Speed	120 m/min
Maximum acceleration	2 m/s ²
Field of application	Dynamic
Minimum dynamic operating bending radius	10 (xD)
操作度范	- 15 ... 80 ° C
Storage temperature, range	- 40 ... 80 ° C
	IEC 60332 - 1 - 2; UL 1581 FT1
Oil resistance	DIN EN 50363 - 10 - 2 & DIN EN 60811 - 404