



For dynamic application, demanding environmental conditions MOTIONLINE® ADVANCED

STANDARDS

Product UL and CSA approval

For dynamic application, demanding environmental conditions; PUR Jacket; resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.

Reference: 48216165

CONTACT

Market information
industryprojects.business@lynxéogroup.com



Halogen free
Yes



Operating temp.
-20 ... 80 °C



Storage temperature, range
-40 ... 80 °C



Flame retardant
IEC 60332-2; FT2



Oil resistance
DIN EN 50363-10-2 & DIN EN 60811-404

CHARACTERISTICS**Construction characteristics**

Construction type	2 x 1.50
Conductor material	Tinned copper
Insulation	TPM
Insulation colour	Brown-Blue
Outer sheath	PUR
Sheath colour	Yellow
Halogen free	Yes

Dimensional characteristics

Copper content	29 kg/km
Approximate weight	61 kg/km

Electrical characteristics

Rated Voltage U ₀ /U	300 V
Test voltage	1500 V

Mechanical characteristics

Bending cycles	5 Mio.
Speed	180 m/min
Maximum acceleration	20 m/s ²

Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	6 (xD)
Operating temperature, range	-20 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Flame retardant	IEC 60332-2; FT2
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404