

# MEASURING SYSTEM CABLES ACC. TO LENZE® STANDARD

MEASURING SYSTEM CABLES LENZE® STANDARD (3x(2x0,14)C +(4x0,14)+(2+0,5))C



Measuring systems cables for very dynamic applications. MOTIONLINE® ADVANCED

## STANDARDS

**Product** UL and CSA approval

For very dynamic applications; PUR Jacket, screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.

**Reference:** 49383570

## CONTACT

Market information  
[industryprojects.business@lynxéogroup.com](mailto:industryprojects.business@lynxéogroup.com)



Halogen free  
**Yes**



Operating temp.  
 -15 ... 80 °C



Storage temperature, range  
 -40 ... 80 °C



Flame retardant  
 IEC 60332-1-2; UL 1581 FT1



Oil resistance  
 DIN EN 50363-10-2 & DIN EN 60811-404

## CHARACTERISTICS

### Construction characteristics

Construction type	(3x(2x0,14)C+(4x0,14)+(2+0,5))C
Conductor material	Bending-resistant conductor with tinned copper wires
Insulation	TPM with very low capacitance
Insulation colour	See Tab
Screen	Tinned copper braid, coverage ≥ 85%
Outer sheath	PUR
Sheath colour	Green RAL 6018
Halogen free	Yes

### Dimensional characteristics

Copper content	50 kg/km
Approximate weight	89 kg/km
Outer Diameter	8.9 mm

### Electrical characteristics

Rated Voltage U <sub>0</sub> /U	30 V
Test voltage	300 V

### Mechanical characteristics

Bending cycles	5 Mio.
Speed	180 m/min
Maximum acceleration	20 m/s <sup>2</sup>

### Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	10 (xD)
Operating temperature, range	-15 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404