



Measuring systems cables for very dynamic applications. MOTIONLINE® ADVANCED

### STANDARDS

**Product** UL and CSA approval

For very dynamic applications; PUR Jacket, screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.

**Reference:** 49389960

**Country Ref.:** IN 280

### CONTACT

Market information  
[industryprojects.business@lynxogroup.com](mailto:industryprojects.business@lynxogroup.com)



Halogen free  
Yes



Operating temp.  
-15 ... 80 °C



Storage temperature, range  
-40 ... 80 °C



Flame retardant  
IEC 60332-1-2; UL 1581 FT1



Oil resistance  
DIN EN 50363-10-2 & DIN EN 60811-404

**CHARACTERISTICS****Construction characteristics**

Construction type	(3x0,25+3x(2x0,25)+2x1,0)C
Conductor material	Bending-resistant conductor with tinned copper wires
Insulation	TPM with very low capacitance
Insulation colour	See Tab
Screen	Tinned copper braid, coverage ≥ 80%
Outer sheath	PUR
Sheath colour	Orange RAL 2003
Halogen free	Yes

**Dimensional characteristics**

Outer Diameter	9.3 mm
Copper content	87 kg/km
Approximate weight	127 kg/km

**Electrical characteristics**

Rated Voltage U <sub>0</sub> /U	30 V
Test voltage	300 V

**Mechanical characteristics**

Bending cycles	10 Mio.
Speed	180 m/min
Maximum acceleration	20 m/s <sup>2</sup>

**Usage characteristics**

Field of application	Dynamic
Minimum dynamic operating bending radius	10 (xD)
Operating temperature, range	-15 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404