



Servo cables for extremely dynamic applications with star quad MOTIONLINE® PREMIUM

### STANDARDS

**Product** UL and CSA approval

Servo cables with star-quad for extremely dynamic applications; PUR jacket, TPE inner jacket, screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.

**Reference:** 49471060

### CONTACT

Market information  
[industryprojects.business@lynxgroup.com](mailto:industryprojects.business@lynxgroup.com)



Halogen free  
Yes



Operating temp.  
-30 ... 80 °C



Storage temperature, range  
-50 ... 80 °C



Flame retardant  
IEC 60332-1-2; UL 1581 FT1



Oil resistance  
DIN EN 50363-10-2 & DIN EN 60811-404

### CHARACTERISTICS

#### Construction characteristics

Construction type	(4G6,0+(4x0,5)C)C
Conductor material	Bending-resistant conductor with bare copper wires
Insulation	TPM with very low capacitance
Lay Up	power cores and control pairs stranded with filler
Insulation colour	Power: 3 black cores with marking, 1 core green-yellow Power: U/L1/C/L+ // V/L2 // W/L3/D/L- // Ye/Gn Star-quad: black - white - red - yellow
Individual screen	Signal shield: Tinned copper braid, coverage $\geq 80\%$
Screen	Tinned copper braid, coverage $\geq 80\%$
Inner sheath	TPE compound, optimized for drag chain use
Outer sheath	PUR
Sheath colour	Orange RAL 2003
Halogen free	Yes

#### Dimensional characteristics

Outer Diameter	17.4 mm
Copper content	335 kg/km
Approximate weight	493 kg/km

#### Electrical characteristics

Rated Voltage U <sub>0</sub> /U	0.6/1 kV
Test voltage	4000 V

#### Mechanical characteristics

Bending cycles	5 Mio.
Speed	300 m/min
Maximum acceleration	50 m/s <sup>2</sup>

#### Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	7.5 (xD)
Operating temperature, range	-30 ... 80 °C
Storage temperature, range	-50 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404