

MEASURING SYSTEM CABLES ACC. TO LENZE® STANDARD

MEASURING SYSTEM CABLES LENZE® STANDARD (3x(2x0,14)C
+ (2x0,5)C)C



Measuring systems cables for very dynamic applications. MOTIONLINE®
ADVANCED

STANDARDS

Product UL and CSA approval

For very dynamic applications; PUR Jacket, screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC - and halogen - free.

Reference: 49480870

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com



Halogen free



Operating temp.
- 15 ... 80 °C



Storage temperature, range
- 40 ... 80 °C



Oil resistance
IEC 60332 - 1 - 2; UL 1581 FT1
DIN EN 50363 - 10 - 2 & DIN EN 60811 - 404

CHARACTERISTICS

	(3x(2x0.14)D+(2x0.5)D)C
	Bending - resistant conductor with tinned copper wires
	TPM with very low capacitance
Insulation colour	See Tab
	Tinned copper braid, coverage 85%
Sheath colour	PUR
Halogen free	Green RAL 6018
Copper content	64 kg/km
()	107 kg/km
	9.3 mm
Rated Voltage U _o /U	30 V
	300 V
Bending cycles	5 Mio.
Speed	180 m/min
Maximum acceleration	20 m/s ²
Field of application	Dynamic
Minimum dynamic operating bending radius	10 (xD)
操作度范	- 15 ... 80 ° C
Storage temperature, range	- 40 ... 80 ° C
	IEC 60332 - 1 - 2; UL 1581 FT1
Oil resistance	DIN EN 50363 - 10 - 2 & DIN EN 60811 - 404