

# MEASURING SYSTEMS CABLES ACC. TO SIEMENS® STANDARD 6FX8008

MEASURING SYSTEMS ACC. TO SIEMENS® 6FX8008 (3x(2x0,14)C+2x0,5+4x0,14)C



Measuring systems cables for very dynamic applications. MOTIONLINE® ADVANCED

## STANDARDS

**Product** UL and CSA approval

For very dynamic applications; PUR Jacket, screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.

**Reference:** 49482971  
**Country Ref.:** 6FX8008-1BD41

## CONTACT

Market information  
 industryprojects.business@lynxéo.com  
 ogroup.com



Halogen free  
 Yes



Operating temp.  
 -15 ... 80 °C



Storage temperature, range  
 -40 ... 80 °C



Flame retardant  
 IEC 60332-1-2; UL 1581 FT1



Oil resistance  
 DIN EN 50363-10-2 & DIN EN 60811-404

**CHARACTERISTICS****Construction characteristics**

Construction type	(3x(2x0,14)C+2x0,5+4x0,14)C
Conductor material	Bending-resistant conductor with tinned copper wires
Insulation	TPM with very low capacitance
Insulation colour	See Tab
Screen	Tinned copper braid, coverage ≥ 85%
Outer sheath	PUR
Sheath colour	Green RAL 6018
Halogen free	Yes

**Dimensional characteristics**

Copper content	61 kg/km
Approximate weight	101 kg/km
Outer Diameter	9.1 mm

**Electrical characteristics**

Rated Voltage U <sub>0</sub> /U	30 V
Test voltage	300 V

**Mechanical characteristics**

Bending cycles	5 Mio.
Speed	180 m/min
Maximum acceleration	20 m/s <sup>2</sup>

**Usage characteristics**

Field of application	Dynamic
Minimum dynamic operating bending radius	10 (xD)
Operating temperature, range	-15 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404