



Reference: 71320702

**CONTACT**

Market information  
 industryprojects.business@lyn  
 xeogroup.com

Torsion resistant low - voltage cable for free hanging of max. 100 m

**STANDARDS**

Product EN 50363; HD 22 - 13; IEC 60228; IEC 60502

**APPLICATIONS**

Low - voltage loop cable WINDLINK LV - RS (N)HXCSLOE was developed for special application condition in wind turbines. The construction is torsion resistant by free hanging of max.100 m. These cables are specified for medium mechanical stress and for operation under permanent influence of sea water and usage outdoor.

Resistance to

- permanent movement
- permanent vibrations
- compressive stress
- oil, EN60811 - 2 - 1, ASTM No.2, 24 h at 100 ° C
- low smoke, IEC 61034, >50 %
- halogen - free IEC 60754
- permanent influence of seawater
- ozone influence, EN 60811 - 2 - 1 clause 8
- suitable for torsion of max. 6 counterclockwise rotations and min. free hanging up from 25 m

**Design**

Core

Conductor

- Copper, plain, flexible concentrically stranded circular

Insulation

- Extruded halogen - free rubber compound E18 acc. to EN 50363 - 5

Screen

- Tinned wire copper braid, covering min. 80 %

Outer Sheath

- Extruded halogen - free EVA compound EM8 acc. to EN 50363 - 6

## CHARACTERISTICS

Conductor flexibility	5
Sheath colour	
Halogen free	IEC 60754 - 2
Overall screen	-
With Green/Yellow core	
	12
	1.5 mm <sup>2</sup>
Copper content	0 kg/km
Nominal outer diameter	16.0 mm
( )	400 kg/km
U <sub>0</sub> /U (Um)	0,6/1 kV
	EN 50265 - 2 - 1
Silicone free	Yes
RoHS compliant	-
Max. conductor temperature in service	- °C
Weather resistance	-
Short - circuit max. conductor temperature	- °C

## SELLING AND DELIVERY INFORMATION

Inkjet marking e.g.: WINDLINK LV - RS (N)HXCSLOE 0.6/1 kV | NEXANS I