



Reference: 79462722

CONTACT

Markets and Products Information
rollingstock.business@lynxeogroup.com

SHIELDED SINGLE CORE POWER CABLES

FLAMEX® EN 50264 - 3 - 1 1800V MMS shielded power cables are used for protected installations where enhanced electrical screening (EMC) is required. This product range is recommended for installations and connections in narrow spaces where an optimal bending radius is required. FLAMEX® cables are designed to withstand tough working conditions (oil, ozone, temperature variation, etc.). 120 ° C conductor temperature is allowed for a 20,000 hours cumulative working time.

STANDARDS

Product EN 50264 - 3 - 1; EN 45545 - HL3; IEC 60228

DESIGN

1. Conductor
Flexible stranded tinned copper, class 5 acc. to IEC 60228
Optional halogen - free separator tape
2. Insulation
Cross - linked compound type EI 109 acc. to EN 50264 - 1
3. Screen
Halogen - free foil, tinned copper wire braid, halogen - free separator
4. Outer sheath
Cross - linked compound type EM 104 acc. to EN 50264 - 1
Oil, diesel, ozone and UV resistant
Colour: black

Example of marking: FLAMEX EN 50264 - 3 - 1 1800V (mm²) MM S (N)
SHXAFCOE 1.8/3 kV | LYNXEO | WW - YYYY

GUIDE TO USE

- Cabling rules are given in EN 50343 and EN 50355
- Permissible current carrying capacities: values and calculation method are given in EN 50343
- Bending radius:
 - Static use: 5 x outer cable diameter (6 x D if D > 10mm)
 - For installation and occasional movements: 10 x outer cable diameter



Conductor flexibility
5



Halogen free
EN 60754 - 1 & EN 60684 - 2



Uo/U
(Um)
1.8 / 3 (3.6) kV



EN 60332 - 1 - 2



Fire retardant
EN IEC 60332 - 3 - 24 (cat C); EN IEC 60332 - 3 - 25 (EN50305)



EN/IEC 61034 - 2



기
EN 50305 - 9.2



Electro magnetic interference resistance
Yes

CHARACTERISTICS

Conductor flexibility	Tin plated copper 5
	Cross - linked compound
Halogen free	Cross - linked compound EN 60754 - 1 & EN 60684 - 2
Minimum outer diameter	10 mm ² 10.1 mm
Maximum outer diameter	10.7 mm
Braid section	6 mm ²
()	208 kg/km
	1
U _o /U (U _m)	1.8 / 3 (3.6) kV
Fire retardant	EN 60332 - 1 - 2 EN IEC 60332 - 3 - 24 (cat C); EN IEC 60332 - 3 - 25 (EN50305)
가	EN/IEC 61034 - 2 EN 50305 - 9.2
Electro magnetic interference resistance	Yes
操作度范	- 40 ... 90 °C
Max. conductor temperature in service	- °C
Overload maximum core temperature	- °C
Chemical resistance	Excellent
Ozone resistance	Yes
U.V resistance	Yes
Fire load	0.35 kWh/m
Short - circuit max. conductor temperature	200 °C