FLAMEX® EN 50264-3-1 MM 1800V

FLAMEX EN 50264-3-1 1800V 35 MM



Reference: 79463024

CONTACT

Markets and Products Information
rollingstock.business@lynxeogroup.com

SHEATHED SINGLE CORE POWER CABLES

FLAMEX® EN 50264-3-1 1800V MM power cables are used for fixed and protected installations. This product range is recommended for narrow spaces where an optimal bending radius is required. FLAMEX® cables are designed to withstand tough working conditions (oil, ozone, temperature variation, etc.). 120°C conductor temperature is allowed for a 20,000 hours cumulative working time.

STANDARDS

Product EN 50264-3-1; EN 45545 - HL3; IEC 60228

DESIGN

1. Conductor
Flexible stranded tinned copper, class 5 acc. to IEC 60228
Optional halogen-free separator tape

2. Insulation
Cross-linked compound type EI 109 acc. to 50264-1.
Colour: grey

3. Sheath
Cross-linked compound type EM 104 acc. to 50264-1
Oil, diesel, ozone and UV resistant
Colour: black

Example of marking: FLAMEX EN 50264-3-1 1800V (mm²) MM NSHXAFOE 1.8/3 kV I LYNXEO I WW-YYYY

GUIDE TO USE

- Cabling rules are given in EN 50343 and EN 50355
- Permissible current carrying capacities: values and calculation method are given in EN 50343
- Bending radius:
  - Static use: 3 x outer cable diameter (5 x D if D>10mm)
  - For installation and occasional movements: 6 x outer cable diameter

Conductor flexibility	Halogen free	Rated Voltage Uo/U (Um)	Flame retardant	Fire retardant	Smoke density	Gases toxicity	Operating temp.
Flexible class 5	**EN 60754-1 & EN 60684-2**	**1.8 / 3 (3.6) kV**	**EN 60332-1-2**	**EN IEC 60332-3-24 (cat C); EN IEC 60332-3-25 (EN50305)**	**EN/IEC 61034-2**	**EN 50305-9.2**	**-40 ... 90 °C**

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Lynxeo is indicative only and shall not be binding on Lynxeo or be treated as constituting a representation on the part of Lynxeo.

FLAMEX® EN 50264-3-1 MM 1800V

FLAMEX EN 50264-3-1 1800V 35 MM

CHARACTERISTICS

Construction characteristics	
Conductor material	Tin plated copper
Conductor flexibility	Flexible class 5
Insulation	Cross-linked compound
Outer sheath	Cross-linked compound
Halogen free	EN 60754-1 & EN 60684-2
Dimensional characteristics	
Conductor cross-section	35 mm²
Minimum outer diameter	13.3 mm
Maximum outer diameter	14.1 mm
Approximate weight	450 kg/km
Conductor diameter	- mm
Electrical characteristics	
Rated Voltage Uo/U (Um)	1.8 / 3 (3.6) kV
Usage characteristics	
Flame retardant	EN 60332-1-2
Fire retardant	EN IEC 60332-3-24 (cat C); EN IEC 60332-3-25 (EN50305)
Smoke density	EN/IEC 61034-2
Gases toxicity	EN 50305-9.2
Operating temperature, range	-40 ... 90 °C
Max. conductor temperature in service	90 °C
Overload maximum core temperature	- °C
Chemical resistance	Excellent
Ozone resistance	Yes
U.V resistance	Yes
Short-circuit max. conductor temperature	200 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Lynxeo is indicative only and shall not be binding on Lynxeo or be treated as constituting a representation on the part of Lynxeo.