



Reference: 79463401

CONTACT

Markets and Products Information
 rollingstock.business@lynxeogroup.com

SINGLE CORE POWER CABLES

FLAMEX® EN 50264-3-1 600V M power cables are used for fixed and protected installations. This product range is recommended for narrow spaces where an optimal bending radius is required. FLAMEX® cables are designed to withstand tough working conditions (oil, ozone, temperature variation, etc.). 120°C conductor temperature is allowed for a 20,000 hours cumulative working time.

STANDARDS

Product EN 50264-3-1; EN 45545 - HL3; IEC 60228

Applications

For protected installation in railway vehicles #locomotives, trains, trolley-busses etc##, switching station and control panels# Installation in cable ducts, pipes and tubes#

Current carrying capacity according to EN 50343 as well as VDE 0298 part 4#

Complies with performance requirements acc# to EN 45545 part 2-HL3#

Design

1# Conductor

Flexible stranded tinned copper, class 5 in acc# with DIN VDE 0295 / EN/IEC 60228, conductor screen

2# Sheath

Cross-linked compound EI 109 acc# to EN 50264-3-1

Oil, diesel-oil, ozone and UV resistant

Colour: black

Cable marking

Printing white; visibly coloured:

FLAMEX EN 50264-3-1 600V mm² M #N#HXAF 0,6/1kV | NEXANS | WW-YYYY
 Retardant acc. to EN 50305



Conductor flexibility
 Flexible class 5



Halogen free
 EN 60754-1 & EN 60684-2



Rated Voltage U₀/U
 (Um)
 0.6/ 1 (1.2) kV



Flame retardant
 IEC 60332-1-2



Fire retardant
 EN IEC 60332-3-24
 (cat C); EN IEC 60332-3-25
 (EN50305)



Smoke density
 EN/IEC 61034-2



Gases toxicity
 EN 50305-9.2



Operating temp.
 -40 ... 90 °C

CHARACTERISTICS**Construction characteristics**

Conductor material	Tin plated copper
Conductor flexibility	Flexible class 5
Insulation	Cross-linked compound
Halogen free	EN 60754-1 & EN 60684-2

Dimensional characteristics

Conductor cross-section	120 mm ²
Minimum outer diameter	16.7 mm
Maximum outer diameter	17.3 mm
Approximate weight	1106 kg/km
Conductor diameter	- mm

Electrical characteristics

Rated Voltage U ₀ /U (U _m)	0.6/ 1 (1.2) kV
---	-----------------

Usage characteristics

Flame retardant	IEC 60332-1-2
Fire retardant	EN IEC 60332-3-24 (cat C); EN IEC 60332-3-25 (EN50305)
Smoke density	EN/IEC 61034-2
Gases toxicity	EN 50305-9.2
Operating temperature, range	-40 ... 90 °C
Max. conductor temperature in service	90 °C
Overload maximum core temperature	- °C
Chemical resistance	Good
Ozone resistance	Yes
U.V resistance	Yes
Short-circuit max. conductor temperature	200 °C