



Reference: EN 2267-009D 090P (DRD 8)

CONTACT

Market information
 industryprojects.business@lynxéogroup.com

International Designation: DRD 8 090

Designed for general Purpose Aircraft Wiring Applications.

Multicores DRA

STANDARDS

Product EN 2267-009

Test prEN 3475

DESIGN CONSTRUCTION

CORES

2, 3 or 4 cores EN2267-009A

IDENTIFICATION

Colours of cores : See table in this datasheet

Colours of marking: White for red and green core, green for blue and yellow cores

Marking : EN DRA ** FR F ++

DRA = short designation

** = AWG

FR = Country of origin (FR = France)

F = Manufacturer (F = Lynxéo)

++ = Year of production (i.e. 14 = 2014)

CHARACTERISTICS

Construction characteristics

Colour	P
Type of conductor	-
Core identification	Red, Blue, Yellow, Green
Number of conductors	-
Size code	-

Dimensional characteristics

Maximum outer diameter	10.56 mm
Nominal outer diameter	10.38 mm
Number of cores	4
Maximum weight	370.8 g/m



Flame retardant
 FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Oil resistance
 Very good resistance to aircraft fluids



RoHS compliant
 Yes



Operating temp.
 -55 ... 260 °C

Dimensional characteristics

Nominal weight	358.26 g/m
----------------	------------

Electrical characteristics

Maximal operating frequency	0.002 MHz
Maximum DC resistance at 20°C	2.37 Ohm/100m
Operating voltage	600 V

Usage characteristics

Flame retardant	FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)
Oil resistance	Very good resistance to aircraft fluids
Arc tracking resistant	Yes
RoHS compliant	Yes
Operating temperature, range	-55 ... 260 °C

IDENTIFICATION

Colours of cores	: See table in this datasheet
Colours of marking	: White for red and green core, green for blue and yellow cores
Marking	: EN DRA ** FR F ++ DRA = short designation ** = AWG FR = Country of origin (FR = France) F = Manufacturer (F = Lynx ^{eo}) ++ = Year of production (i.e. 14 = 2014)



Flame retardant
FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Oil resistance
Very good resistance to aircraft fluids



RoHS compliant
Yes



Operating temp.
-55 ... 260 °C