



Reference: EN 2267-010A 020 S
Country Ref.: 10061896

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

International Designation: EN 2267-010A 020

DR14

STANDARDS

Product EN 2267-010

KEY CHARACTERISTICS

电气特性

20° C时导体的最大直流电阻

10.9 Ohm/km

DESIGN CONSTRUCTION

CORE

Stranded Conductor : Nickel Plated High

Strength Copper Alloy (AWG 26 & 24) or
Nickel Plated Copper (AWG 22 to 2)

INSULATION

Special Polyimide Tape
Special UV PTFE Tape(s)

IDENTIFICATION

Standard colour code :

White except AWG 26 which is light yellow and AWG 22 which is light green
AWG 24 is available in light blue color (EN2267-010A 002B)

Color of marking: green

Marking text: EN DR ** FR F ++

DR = Short designation

** = AWG Wire Size

FR = Country of origin (FR = France)

F = Manufacturer (F = Lynx^{eo})

++ = Year of production (i.e. 13 = 2013)



操作温度
-55 ... 260 ° C



耐油
Very good resistance to aircraft fluids

CHARACTERISTICS

结构特性

颜色	S
导体类型	Stranded Conductor: Nickel plated alloy
导体材料	镀镍铜线
绝缘材料	Special Polyimide Tape, Special UV PTFE Tape(s)
Size code	

尺寸特性

最大线缆直径	2.24 mm
最小线缆直径	2.04 mm
Maximum outer diameter	1.73 mm
外径最小值	1.69 mm
导体横截面尺寸 (AWG)	14
Conductor stranding	37 x 0.25
最大重量	19.78 g/m
标称重量	19.31 g/m

电气特性

最大工作频率	0.002 MHz
20° C时导体的最大直流电阻	10.9 Ohm/km
Operating Voltage Vo DC	28 V
Operating voltage between phases	200 V
Operating voltage between phase and neutral	115 V

使用特性

操作温度范围	-55 ... 260 ° C
耐油	Very good resistance to aircraft fluids
Arc tracking resistant	是