



Reference: Etude 133528
Country Ref.: Etude 133528

CONTACT

Market information
 industryprojects.business@lynxgroup.com

International Designation:

3 channels 32 AWG coax
 + 4 x 26 AWG wires

Monitoring cable assemblies

Very flexible cable with an extremely good mechanical behaviour.
 Withstands miscellaneous sterilisation processes.

STANDARDS

Product 448-010-3-10; Nexans specification

1- CORE (A)

AWG 32 stranded Silver plated copper alloy conductor.
 FEP insulation.
 Diameter : 0.65 +/- 0.02 mm.
 AWG 44 Silver plated copper spiral shield.
 Nominal diameter : 0.75 mm.
 FEP jacket
 Diameter : 0.91 +/- 0.03 mm

2- CORE (B)

AWG 26 stranded Silver plated copper conductor.
 FEP insulation.
 Diameter : 0.91 +/- 0.05 mm

Assembly

1 Filler + 1 Kevlar member
 Around 3 Cores (A) + 4 Cores (B) twisted.
 Nominal diameter : 3.00 mm

3- PTFE Tape

Nominal diameter : 3.07 mm

4- SHIELD

AWG 40 Silver plated copper braid.
 85% coverage.
 Nominal diameter : 3.43 mm

5- JACKET

Medical PVC
 Diameter : 6.80 +/- 0.15 mm

Main Characteristics

Minimum bending radius : 5 x Overall diameter.



Cable flexibility
Very flexible



Maximum operating temperature
85 °C



Minimum operating temperature
-30 °C



RoHS compliant
Yes

CHARACTERISTICS**Construction characteristics**

Construction type	Shielded and sheathed
Conductor shape	Single wired
Conductor material	Silver coated copper
Insulation	FEP

Dimensional characteristics

Approximate weight	62 g/m
Outer Diameter	6.8 mm

Electrical characteristics

Operating voltage	24 V
-------------------	------

Mechanical characteristics

Cable flexibility	Very flexible
-------------------	---------------

Usage characteristics

Maximum operating temperature	85 °C
Minimum operating temperature	-30 °C
RoHS compliant	Yes