



Reference: Etude 133652

CONTACT

Market information
 industryprojects.business@lynxegroup.com

International Designation:
 68 channels 38 AWG coax cable

Ultrasound cable assemblies

Very flexible cable with an extremely good mechanical behaviour.
 Withstands miscellaneous sterilisation processes.

STANDARDS

Product Nexans specification

1- CORE (A)

AWG 38 silver plated copper wire.
 FEP insulation.
 Diameter : 0.30 +/- 0.02 mm
 AWG 48 silver plated copper helicoidal screen
 Nominal diameter : 0.36 mm
 FEP jacket
 Diameter : 0.46 +/- 0.03 mm

2- CORE (B)

8 Cores A twisted.
 Nominal diameter : 1.40 mm

3- CORE (C)

2 Cores (A) twisted.
 Nominal diameter : 0.90 mm

1 Kevlar strength member +
 8 Cores (B) + 2 Cores (C) twisted.
 Nominal diameter : 4.60 mm

4- PTFE Tape

Nominal diameter : 4.65 mm

5- SHIELD

AWG 40 tin plated copper braid.
 85% coverage.
 Max. diameter : 5.23 mm

Main Characteristics

Minimum bending radius : 5 x Overall diameter.



Cable flexibility
Very flexible



Maximum operating temperature
105 °C



Minimum operating temperature
-30 °C



RoHS compliant
Yes

CHARACTERISTICS**Construction characteristics**

Construction type	Shielded and sheathed
Conductor shape	Single wired
Conductor material	Silver coated copper
Insulation	FEP

Dimensional characteristics

Approximate weight	50 g/m
Outer Diameter	5.03 mm

Electrical characteristics

Operating voltage	24 V
-------------------	------

Mechanical characteristics

Cable flexibility	Very flexible
-------------------	---------------

Usage characteristics

Maximum operating temperature	105 °C
Minimum operating temperature	-30 °C
RoHS compliant	Yes