



CONTACT

Market information
industryprojects.business@lynx
ogroup.com

- Instrumentation cables 170/300 V
- With lead cover (LC)
- Overall Screen (OS)
- **Aliphatic and aromatic hydrocarbons resistant**

STANDARDS

Test IEC 60331; IEC 60332-3-22 Cat.A

APPLICATIONS

These instrumentation and communication cables are used to **transmit analogue or digital signals in measurement and process control**. They are well adapted to **underground use** in industrial applications, in moist areas, where **hydrocarbon and mechanical protection are needed**. The **lead cover brings an enhanced resistance to aromatics hydrocarbons**. They maintain circuit integrity when exposed to fire.

Design

Conductor:

Stranded bare copper class 2

Insulation:

Silicone rubber (Sil)

Overall screen:

Polyester tape

Tinned copper drain wire,

Aluminium backed polyester tape

Inner sheath:

Low Smoke Zero Halogen (LSZH)

Colour: black

Lead sheath

Bedding (intermediate sheath):

Polyvinyl chloride (PVC)

Colour: black

Armour:

Galvanized steel wires (SWA)

Outer sheath:



Rated Voltage Uo/U
(Um)
170/300V



Mechanical
resistance to
impacts
Good



Fire
resistance
IEC 60331



Polyvinyl chloride (PVC)
Colour: black



Chemical
resistance
**Aliphatic and
aromatic
hydrocarbons
resistant**



Electro magnetic
interference
resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor
temp. in service
90 °C

Core identification

Pair: white - black

Quad: white - black - red - blue (2 pair cables assembled as a quad)

All Whites designates with pair number
White core designates with pair number
and particulars of weights, size and dimensions
contained in the technical or commercial documentation of Lynx^{eo} is indicative only and shall not be
binding on Lynx^{eo} or be treated as constituting a representation on the part of Lynx^{eo}.

Marking

NEXANS 279 SIL/OA.SCR/LSZH//LC/PVC/SWA/PVC 170/300V Nber of pairs & cross-

CHARACTERISTICS

Construction characteristics

Conductor material	Bare copper
Type of conductor	Stranded, class 2
Insulation	Silicone rubber
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Inner sheath	Low smoke, zero halogen thermoplastic compound
Lead Sheath	Yes
Intermediate sheath	PVC
Armour type	Galvanized steel wires
Outer sheath	PVC
Protection	Yes

Dimensional characteristics

Number of pairs	10
Conductor cross-section	0.75 mm ²
Conductor diameter	1.1 mm
Diameter over insulation	2.26 mm
Diameter over inner sheath	18 mm
Diameter over lead sheath	20.4 mm
Diameter over intermediate sheath	22.4 mm
Diameter over armour	24.9 mm
Minimum outer diameter	25.5 mm
Maximum outer diameter	29.7 mm
Approximate weight	1968 kg/km

Electrical characteristics

Rated Voltage U ₀ /U (Um)	170/300V
--------------------------------------	----------

Mechanical characteristics

Mechanical resistance to impacts	Good
----------------------------------	------

Usage characteristics

Fire resistant	IEC 60331
Fire retardant	EN IEC 60332-3-22 (cat A)
Chemical resistance	Aliphatic and aromatic hydrocarbons resistant
Electro magnetic interference resistance	Yes
Operating temperature, range	-20 ... 60 °C
Max. conductor temperature in service	90 °C
Standard	EN



Rated Voltage U₀/U (Um)
170/300V



Mechanical resistance to impacts
Good



Fire resistant
IEC 60331



Fire retardant
EN IEC 60332-3-22 (cat A)



Chemical resistance
Aliphatic and aromatic hydrocarbons resistant



Electro magnetic interference resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor temp. in service
90 °C

SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) on request.

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

Tinned copper conductors available on request



Rated Voltage U₀/U
(Um)
170/300V



Mechanical
resistance to
impacts
Good



Fire resistant
IEC 60331



Fire retardant
**EN IEC 60332-3-22
(cat A)**



Chemical
resistance
**Aliphatic and
aromatic
hydrocarbons
resistant**



Electro magnetic
interference
resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor
temp. in service
90 °C