



## CHARACTERISTICS

### Construction characteristics

Conductor material	Bare copper
Type of conductor	Stranded, class 2
Insulation	Silicone rubber
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Inner sheath	Low smoke, zero halogen thermoplastic compound
Lead Sheath	Yes
Intermediate sheath	PVC
Armour type	Galvanized steel wires
Outer sheath	PVC
Protection	Yes

### Dimensional characteristics

Number of pairs	10
Conductor cross-section	2.5 mm <sup>2</sup>
Conductor diameter	1.91 mm
Diameter over insulation	3.07 mm
Diameter over inner sheath	23.6 mm
Diameter over lead sheath	26.2 mm
Diameter over intermediate sheath	28.6 mm
Diameter over armour	31.8 mm
Minimum outer diameter	32.0 mm
Maximum outer diameter	37.4 mm
Approximate weight	3169 kg/km

### Electrical characteristics

Rated Voltage U <sub>0</sub> /U (Um)	170/300V
--------------------------------------	----------

### Mechanical characteristics

Mechanical resistance to impacts	Good
----------------------------------	------

### Usage characteristics

Fire resistant	IEC 60331
Fire retardant	EN IEC 60332-3-22 (cat A)
Chemical resistance	Aliphatic and aromatic hydrocarbons resistant
Electro magnetic interference resistance	Yes
Operating temperature, range	-20 ... 60 °C
Max. conductor temperature in service	90 °C
Standard	EN



Rated Voltage U<sub>0</sub>/U (Um)  
170/300V



Mechanical resistance to impacts  
Good



Fire resistant  
IEC 60331



Fire retardant  
EN IEC 60332-3-22 (cat A)



Chemical resistance  
Aliphatic and aromatic hydrocarbons resistant



Electro magnetic interference resistance  
Yes



Operating temp.  
-20 ... 60 °C



Max. conductor temp. in service  
90 °C

**SELLING AND DELIVERY INFORMATION**

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) on request.

Minimum bending radius:

10 x outer diameter  
To be doubled during laying operations

Tinned copper conductors available on request



Rated Voltage U<sub>0</sub>/U  
(Um)  
**170/300V**



Mechanical  
resistance to  
impacts  
**Good**



Fire resistant  
**IEC 60331**



Fire retardant  
**EN IEC 60332-3-22  
(cat A)**



Chemical  
resistance  
**Aliphatic and  
aromatic  
hydrocarbons  
resistant**



Electro magnetic  
interference  
resistance  
**Yes**



Operating temp.  
**-20 ... 60 °C**



Max. conductor  
temp. in service  
**90 °C**