



- Compensation cables 300/500(600) V
- CST 74C068
- Zero halogen (SH)
- Cables installed outside of the containment area (K3)
- Overall Screen (EG)
- Unarmoured (NA)

STANDARDS

Product IEC 60584 - 3; NF C42 - 324

Test IEC 60332 - 3 - 23; IEC 60754 - 1; IEC 61034 - 2; NF C32 - 070/C1

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

CHARACTERISTICS

	Copper Braid
Halogen free	IEC 60754 - 1
	1 mm ²
	1.3 mm
Diameter over insulation	2.5 mm
Diameter over screen	9.9 mm
Minimum outer diameter	11.9 mm
Maximum outer diameter	13.6 mm
()	188 kg/km
Uo/U (Um)	300/500 V
Fire retardant	NF C 32070 C1; IEC 60332 - 3 - 24 (cat.B)
	EN/IEC 61034 - 2
Electro magnetic interference resistance	Yes



Halogen free
IEC 60754 - 1



Uo/U (Um)
300/500 V



Fire retardant
NF C 32070 C1; IEC
60332 - 3 - 24 (cat.B)



EN/IEC 61034 - 2



Electro magnetic
interference
resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor
temp.in service
90 °C

操作度范

- 20 ... 60 ° C

Max. conductor temperature in service

90 ° C

Nuclear Classification

Class 1 E Non LOCA/K3

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations



Halogen free
IEC 60754 - 1



Uo/U (Um)
300/500 V



Fire retardant
NF C 32070 C1; IEC
60332 - 3 - 24 (cat.B)



EN/IEC 61034 - 2



Electro magnetic
interference
resistance
Yes



Operating temp.
- 20 ... 60 ° C



Max. conductor
temp. in service
90 ° C