



CONTACT

Market information
industryprojects.business@lynxgroup.com

- Medium voltage cables 6/10 (12) kV
- CST 74C068
- Zero halogen (SH)
- **Cables installed outside of the containment area (K3)**
- Unarmoured (NA)

STANDARDS

Product IEC 60228; IEC 60502-2

Test IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

APPLICATIONS

These medium voltage cables are used for medium voltage power supply,

DESIGN

Design

Conductor:

Stranded bare copper or aluminium (class 2)

Screen:

Semi-conductor

Insulation:

Ethylene Propylene Rubber (EPR)

Insulation screen:

Semi-conductor

Copper tape

Assembling sheath:

Halogen free

Outer sheath:

Low smoke, zero halogen (LSZH)

Colour: Black

Core identification

1x: natural

3x: black - green - brown (by tape under copper screen)

Marking

LYN^{EO} 279 Nber of cores & cross-section Cu/Al CST 74 C 068 00 K3 SH 6/10(12) kV YYY YYY YYY YYY Manufacturing number + metric marking



Halogen free
 IEC 60754-1



Rated Voltage U_o/U_i (Um) (Fire resistant)
 6 / 10 (12) kV



STANDARD
 NF C32-070-C1, IEC 60332-3-24 (cat.B)



Smoke density
 EN/IEC 61034-2



Operating temp.
 -20 ... 60 °C



Max. conductor temp.in service
 90 °C

Standard

IEC 60332-3-23(B)

CHARACTERISTICS

Construction characteristics

Conductor material	Plain copper
Type of conductor	Stranded, class 2
Insulation	Halogen-free
Outer sheath	Halogen-free
Halogen free	IEC 60754-1

Dimensional characteristics

Conductor cross-section	50 mm ²
Number of cores	3
Minimum outer diameter	47.3 mm
Maximum outer diameter	52.2 mm
Approximate weight	3820 kg/km

Electrical characteristics

Rated Voltage U ₀ /U (U _m)	6 / 10 (12) kV
---	----------------

Usage characteristics

Fire retardant	NF C 32070 C1; IEC 60332-3-24 (cat.B)
Smoke density	EN/IEC 61034-2
Operating temperature, range	-20 ... 60 °C
Max. conductor temperature in service	90 °C
Nuclear Classification	Class 1 E Non LOCA/K3

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

- 1 core: 10 x outer diameter
- Multi: 8 x outer diameter
- To be doubled during laying operations



Halogen free
IEC 60754-1



Rated Voltage U₀/U (U_m)
6 / 10 (12) kV



Fire retardant
NF C 32070 C1; IEC 60332-3-24
(cat.B)



Smoke density
EN/IEC 61034-2



Operating temp.
-20 ... 60 °C



Max. conductor temp.in
service
90 °C