



CONTACT

Market information
industryprojects.business@lynx^{eo}
ogroup.com

- Medium voltage cables 6/10 (12) kV
- CST 74C068
- Zero halogen (SH)
- **Cables installed inside of the containment area (K1)**
- Unarmoured (NA)

STANDARDS

Product IEC 60228; IEC 60502-2

Test IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

APPLICATIONS

These medium voltage cables are used for medium voltage power supply,

DESIGN

Design

Conductor:

Stranded bare copper or aluminium (class 2)

Screen:

Semi-conductor

Insulation:

Ethylene Propylene Rubber (EPR)

Insulation screen:

Semi-conductor

Copper tape

Assembling sheath:

Halogen free

Outer sheath:

Low smoke, zero halogen (LSZH)

Colour: Black


Core identification



Halogen free
IEC 60754-1



Rated Voltage Uo/U
(Um)
6 / 10 (12) kV



1x: natural
3x: black - green - brown (by tape under copper screen)



Smoke density
EN/IEC 61034-2



Life cycle 60years
Yes



Radiation resistant
Yes



LOCA
Yes



Max. conductor
temp. in service
90°C

Marking

LYN^{EO} 279 Nber of cores & cross-section Cu/Al CST 74 C 068 00 K1 SH 6/10(12)
kV YYYY Manufacturing number + metric marking

STANDARDS

Standard

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained herein are for information only or commercial documentation of Lynx^{eo} is indicative only and shall not be binding on Lynx^{eo} or be treated as constituting a representation on the part of Lynx^{eo}.

CHARACTERISTICS

Construction characteristics

Conductor material	Aluminum
Type of conductor	Stranded, class 2
Insulation	Halogen-free
Outer sheath	Halogen-free
Halogen free	IEC 60754-1

Dimensional characteristics

Conductor cross-section	630 mm ²
Number of cores	1
Diameter over screen	- mm
Minimum outer diameter	49.6 mm
Maximum outer diameter	54.7 mm
Approximate weight	3749 kg/km

Electrical characteristics

Rated Voltage U ₀ /U (Um)	6 / 10 (12) kV
--------------------------------------	----------------

Usage characteristics

Fire retardant	NF C 32070 C1; IEC 60332-3-24 (cat.B)
Smoke density	EN/IEC 61034-2
Life cycle 60years	Yes
Radiation resistant	Yes
Loss of coolant accident resistant	Yes
Max. conductor temperature in service	90 °C
Operating temperature, range	-20 ... 60 °C
Nuclear Classification	Class 1 E LOCA /K1

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

- 1 core: 10 x outer diameter
- Multi: 8 x outer diameter
- To be doubled during laying operations



Halogen free
IEC 60754-1



Rated Voltage U₀/U (Um)
6 / 10 (12) kV



Fire retardant
NF C 32070 C1;
IEC 60332-3-24
(cat.B)



Smoke density
EN/IEC 61034-2



Life cycle 60years
Yes



Radiation resistant
Yes



LOCA
Yes



Max. conductor
temp.in service
90 °C